


# Quectel RG651E-NA

## IoT/ eMBB-Optimized LGA 5G Sub-6 GHz and mmWave Module



Quectel RG651E-NA is a 5G LGA module optimized specially for IoT and eMBB applications. Adopting the 3GPP Rel-17 technology, it supports both 5G NSA and SA modes with Option 3x/ 3a/ 3 and Option 2 network architectures, and is backward compatible with the 4G network. The module can meet customers' different application demands for high speed, large capacity, low latency, high reliability, etc.

RG651E-NA is an industrial-grade module for industrial and commercial applications only.

RG651E-NA supports Qualcomm® IZat™ location technology Gen9C Lite (GPS, GLONASS, BDS, Galileo and QZSS). The integrated GNSS receiver greatly simplifies product design and provides quicker, more accurate and more dependable positioning capability.

A rich set of Internet protocols, industry-standard interfaces (USB 2.0/ 3.0/ 3.1, PCIe 3.0, PCM, UART, etc.) and abundant functionalities (USB drivers for Windows, Linux and Android) extend the applicability of the module to a wide range of IoT and eMBB applications such as business routers, home gateway, STB, industrial laptops, consumer laptops, industrial PDA, rugged tablet PCs and video transmission.



### Key Features

- ✓ 5G/ 4G multi-mode module with LGA package, optimized for IoT and eMBB applications
- ✓ Worldwide 5G and LTE-A coverage
- ✓ 5G NSA and SA modes
- ✓ Multi-constellation GNSS receiver (optional) available for applications requiring fast and accurate fixes in any environment
- ✓ Feature refinements: DFOTA and VoNR\* / VoLTE\* (optional)



5G NR Sub-6 GHz and mmWave



LTE Cat 20 (DL)  
LTE Cat 18 (UL)



VoNR\* /VoLTE\* (optional)



Embedded Abundant Protocols



LGA Package



Multi-constellation GNSS (optional)



USB 3.1 High Speed Interface



PCIe 3.0 Interface



Quectel Enhanced AT Commands



RoHS Compliant

# Quectel RG651E-NA

5G Sub-6 GHz & mmWave		RG651E-NA
Region/ Operator	North America	
Dimensions (mm)	46.0 × 53.0 × 3.05	
Weight (g)	TBD	
Temperature Range		
Operating Temperature	-30 °C to +75 °C	
Extended Temperature	-40 °C to +85 °C	
Frequency Bands		
	5G NR	3GPP Rel-17 NSA/ SA operation, Sub-6 GHz and mmWave
	5G NR NSA	n2/ 5/ 7/ 12/ 13/ 14/ 25/ 26/ 29/ 30/ 38/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 257 <sup>②</sup> / 258 <sup>②</sup> / 260 <sup>②</sup> / 261 <sup>②</sup>
5G	5G NR SA	n2/ 5/ 7/ 12/ 13/ 14/ 25/ 26/ 29/ 30/ 38/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 257 <sup>②</sup> / 258 <sup>②</sup> / 260 <sup>②</sup> / 261 <sup>②</sup>
	DL 4 × 4 MIMO	n2/ 5/ 7/ 12/ 13/ 14/ 25/ 26/ 29/ 30/ 38/ 41/ 48/ 66/ 70/ 71/ 77/ 78/ 257 <sup>②</sup> / 258 <sup>②</sup> / 260 <sup>②</sup> / 261 <sup>②</sup>
	8RX* (optional)	n38/ 41/ 48/ 77/ 78
	LTE Category	Cat 20 (DL)/ Cat 18 (UL)
LTE	LTE-FDD	B2/ 4/ 5/ 7/ 12 (17)/ 13/ 14/ 25/ 26/ 29/ 30/ 66/ 71
	LTE-TDD	B38/ 41/ 42/ 43/ 48
	DL 4 × 4 MIMO	B2/ 4/ 5/ 7/ 12 / 13/ 14/ 17/ 25/ 26/ 29/ 30/ 38/ 41/ 42/ 43/ 48/ 66/ 71
GNSS (optional)	GPS/ GLONASS/ BDS/ Galileo/ QZSS	
Certifications		
Regulatory	TBD	
Carrier	TBD	
Others	RoHS	
Data Rates (Max.) <sup>①</sup>		
5G SA Sub-6	7.01 Gbps (DL)/ 1.25 Gbps (UL)	
5G NSA Sub-6	5.47 Gbps (DL)/ 730 Mbps (UL)	
5G NSA mmWave	9.41 Gbps (DL)/ 3.66 Gbps (UL)	
5G SA mmWave	8.61 Gbps (DL)/ 3.54 Gbps (UL)	
5G TDD + mmWave	10.95 Gbps (DL)/ 4.79 Gbps (UL)	
5G FDD + mmWave	9.54 Gbps (DL)/ 3.79 Gbps (UL)	
LTE	2.0 Gbps (DL)/ 211 Mbps (UL)	
Interfaces		
(U)SIM	1.8/ 3.0 V × 1; 1.8 V × 1 (eSIM external)	
UART	× 3	
USB 2.0/ 3.0/ 3.1	× 1	
PCIe 3.0	2-Lane × 2, 1-Lane × 1	
PCM*	× 2	
I2C	× 2	
SPI	× 2	
ADC	●	
RESET_N*	●	
GPIO (QuecOpen <sup>®</sup> )	●	
Antenna	Sub-6 GHz: × 8; GNSS: × 1; mmWave: × 8	

NOTE:

- ①: The presented data rates are theoretical only, and actual values depend on network conditions.
- ②: with mmWave antenna.
- \*: Under development/ In progress.
- : Supported.

# Quectel RG651E-NA

5G Sub-6 GHz & mmWave		RG651E-NA
<b>Audio</b>		
<b>Audio</b>	Digital Audio	VoLTE* / VoNR* (Optional)
<b>Enhanced Features</b>		
<b>DTMF*</b>	●	
<b>DFOTA</b>	●	
<b>(U)SIM Card Detection</b>	●	
<b>Drivers</b>		
<b>USB Serial Driver</b>	Windows 8/ 8.1/ 10/ 11;	Linux 2.6–6.5; Android 4.x–13.x
<b>GNSS Driver</b>	Android 4.x–13.x	
<b>RIL Driver</b>	Android 4.x–13.x	
<b>USB NDIS Driver</b>	Windows 8/ 8.1/ 10/ 11	
<b>USB MBIM Driver</b>	Windows 8/ 8.1/ 10/ 11;	Linux 3.18–6.5
<b>USB GobiNet Driver</b>	Linux 2.6–6.5	
<b>USB QMI_WWAN Driver</b>	Linux 3.4–6.5	
<b>PCIe MHI Driver</b>	Linux 3.10–6.5	
<b>Electrical Features</b>		
<b>Supply Voltage Range</b>	3.3–4.4 V, typ. 3.8 V	
<b>Output Power</b>	<b>5G NR:</b> - Class 1.5 (29 dBm +2/ -3 dB) for n38/ 41/ 77/ 78 - Class 2 (26 dBm +2/ -3 dB) for n2/ 5/ 7/ 25/ 38/ 41/ 66/ 71*/ 77/ 78 - Class 3 (23 dBm ±2 dB) for Other Sub-6 bands <b>LTE:</b> - Class 2 (26 dBm +2/ -3 dB) for B38/ 41/ 42/ 43 - Class 3 (23 dBm ±2 dB) for Other LTE bands	
<b>Power Consumption</b>	TBD	

NOTE:

1. \*: Under development/ In progress.
2. ●: Supported.
3. TBD: To Be Determined.