



Build a smarter world

■ ■ ■ Global IoT solutions provider

Quectel antennas

→ For more information please visit Quectel.com

Contents

Introduction 01

Quectel antennas	01
R&D - Quectel	01
Manufacturing – Quectel and partners	01
Quectel antenna services	02
Quectel advantages	02
Instruments	02

External antennas 03

5G antennas	03
4G antennas	13
Wi-Fi antennas	22
Combo antennas	29
GNSS antennas	45
NTN antennas	52
LPWA/ISM antennas	53
Small cell antennas	59

Embedded antennas 62

5G antennas	62
4G antennas	67
Wi-Fi antennas	77
Combo antennas	84
GNSS antennas	86
NTN antennas	105
LPWA/ISM antennas	107

Cables & Connectors 112

Cables	112
Connections	117

Accessories 118

Other 119

Quectel antennas

Quectel is a leading global provider of IoT antenna solutions, with a team of over 100 experienced antenna R&D engineers worldwide. Our global facilities include 22 testing chambers and fully equipped laboratories, enabling us to deliver end-to-end services—from antenna design and testing to production.

With a portfolio of more than 5,000 antenna products and over 6,000 completed IoT projects, our offerings cover a wide range of applications, including cellular, short-range, GNSS, and automotive antennas. We also specialize in custom antenna design services tailored to specific client needs.

Our global R&D network includes eight advanced centers located in cities such as Belgrade, Shanghai, Hefei and Vancouver. These centers

are equipped with cutting-edge laboratories that support comprehensive testing services, including EMC and OTA testing, ensuring optimal antenna reliability.

We adhere to stringent quality control standards, holding certifications such as ISO 9001 and ISO 14001, with industrial defect rates maintained at $\leq 1,000$ DPPM and automotive defect rates at ≤ 100 DPPM.

In addition, we offer comprehensive RF front-end solutions, full-spectrum RF antenna testing services, and global one-stop engineering support. All our antennas are fully compatible with Quectel modules, allowing customers to source a complete hardware solution from a single, trusted supplier.

R&D - Quectel



 Belgrade



 Penang



 Vancouver

Manufacturing – Quectel and partners



 Changzhou



 Linyi



 Delhi



 Penang

Quectel antenna services



Consulting & evaluation

- Feasibility & architecture study
- Risk identification
- Initial proof of concept
- Antenna type selection



Design

- Antenna placement
- Layout design
- RF specification design
- Multi-antenna design & optimization
- Gerber file review



Testing & certification


- Antenna OTA testing
- Interference mitigation
- Pre-OTA testing for CE/ FCC/ PTCRB




Manufacturing

- Antenna samples
- Tooling & molding
- Assembly and production test
- Delivery


Quectel advantages



Instruments




5G mmWave chamber



Rhode & Schwarz WPTC-XS



RayZone2800



ETS-AMS-8923-195

EXTERNAL

5G antennas



YECN009AA



YECN028AA



YECA001L1AH



YECN001J1A



YECT001W1AM



YECA000G1AM



YFCX001WWAH



YECT010W7AM





YECT005G3AM

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	AVG. 45%
Peak gain	4.6dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	15.6 × 13 × 130mm
Form factor	Rubber
Mounting type	Terminal
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	200mm
Operation temperature	–40°C to +85°C



YECT001W1AM

5G terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	30%–75%
Peak gain	2.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle SMA male
IP rating	IP53
Operation temperature	–40°C to +85°C



YECT001W1BM

5G terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	35%–80%
Peak gain	4.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø9 × 54.9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP65
Operation temperature	–40°C to +85°C



YECT010W1AM

5G terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

700–960 MHz, 1710–2690 MHz, 3300–6000 MHz
AVG. 50%
3.0dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Operation temperature

Ø 10.22 × 69.5mm
Rubber
Terminal
SMA male
–40°C to +85°C



YECT004W1A

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–6000 MHz
20%–70%
5.6 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
IP rating
Operation temperature

135 × 15.6 × 13 mm
Rubber
Terminal
SMA male
IP67
–40°C to +85°C



YECT004W5AM

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–6000 MHz
20%–70%
5.7 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
IP rating
Operation temperature

140 × 15.6 × 13 mm
Rubber
Terminal
Fakra female Code Z
IP67
–40°C to +85°C



YECT104WAAM

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	20%–68%
Peak gain	5.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø20 × 145 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	–40°C to +85°C



YECT005W1A

5G terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	600–6000 MHz
Efficiency	52% AVG.
Peak gain	3.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YECT005WFA

5G terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	600–6000 MHz
Efficiency	50% AVG.
Peak gain	4.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
Operation temperature	–40°C to +85°C



YECT005W1W

5G terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	600-6000 MHz
Efficiency	55% AVG.
Peak gain	4.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	-40°C to +85°C



YE0007AA

5G terminal mount rubber dipole external antenna

Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	600-6000 MHz
Efficiency	40%~85%
Peak gain	4.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	152.4 × 21.79 × 14.49 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	-40°C to +85°C



YECT005W1AM

5G terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	600-6000 MHz
Efficiency	50% AVG.
Peak gain	2.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Φ13 × 196.2 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	-20°C to +70°C



YECN009AA

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	30%–80%
Peak gain	3.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	200 × 21 × 8 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YECN028AA

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410–470 MHz, 617–960 MHz, 1427–6000 MHz
Efficiency	25%–80%
Peak gain	5.8 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	225 × 54.5 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP66
Operation temperature	–40°C to +85°C



YECT028W1A

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	45%–85%
Peak gain	5.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	225 × 54.5 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP66
Operation temperature	–40°C to +80°C



YECT102WAAH

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	45%–85%
Peak gain	5.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	231 × 54.5 × 14.5 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	TNC male
IP rating	IP66
Operation temperature	–40°C to +85°C



YECT103W7AH

5G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	45%–85%
Peak gain	5.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	233 × 54.5 × 20 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	N type male
IP rating	IP66
Operation temperature	–40°C to +85°C



YECT002W1A

5G terminal mount rubber dipole external antenna
Compatible with Japan market

Compliant

RoHS & REACH

Electrical data

Frequency range	600–5000 MHz
Efficiency	55% AVG.
Peak gain	2.8 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	209 × 42 × 6 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–20°C to +60°C



YFCX001WWAH

5G adhesive mount transparent film + cable dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	700–960 MHz, 1450–2690 MHz, 3300–6000 MHz
Efficiency	30%–70%
Peak gain	6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	118.2 × 42.7 mm
Form factor	Transparent film + cable
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	108 mm
Operation temperature	–40°C to +85°C



YECT000WBA

5G screw mount stubby monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1400–2690 MHz, 3300–6000 MHz
Efficiency	20%–90%
Peak gain	8.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø40.6 × 104 mm
Form factor	Stubby
Mounting type	Screw
Connector type	N type female
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YECT101W7AH

5G terminal mount stubby monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1400–2690 MHz, 3300–6000 MHz
Efficiency	20%–90%
Peak gain	8.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø40.6 × 78 mm
Form factor	Stubby
Mounting type	Terminal
Connector type	N type male
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YECN001J1A

5G screw mount stubby monopole external antenna
Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1400–2690 MHz, 3300–6000 MHz
Efficiency	30%–90%
Peak gain	8.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø40.6 × 104 mm
Form factor	Stubby
Mounting type	Screw
Connector type	SMA male
Cable type	ALSR200
Cable length	300 mm
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YECN001L1AH

5G screw mount stubby monopole external antenna
Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1400–6000 MHz
Efficiency	65% AVG.
Peak gain	5.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø40.6 × 104 mm
Form factor	Stubby
Mounting type	Screw
Connector type	SMA male
Cable type	ALSR200
Cable length	1000 mm
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YECA000G1AM

5G adhesive mount low profile dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz, 3300–6000 MHz
Efficiency	35%–80%
Peak gain	4.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	116.5 × 21.7 × 5.6 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	215 mm
Operation temperature	–40°C to +85°C



YECM001L1AH

5G magnetic mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	30%–65%
Peak gain	6.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 82.2 mm
Form factor	Whip
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YECA001L1AH

5G adhesive mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	30%–65%
Peak gain	6.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 83.2mm
Form factor	Whip
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YECT010W7AM

5G terminal mount fiberglass dipole external antenna

Compliant

RoHS & REACH

Electrical data


Frequency range	600-960 MHz, 1400-2700 MHz, 3300-5000 MHz
Efficiency	45%–85%
Peak gain	7.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø25.5 × 300 mm
Form factor	Fiberglass
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	–40°C to +85°C

EXTERNAL

4G antennas



YECT003W1A



YECW000N1A



YECT011W1AM



YECA000M1A



YECM002L1AH



YE0006AA



YECT001W1CM



YECT009W1AM





YECT012G3AM

4G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	700–960 MHz, 1710–2690 MHz
Efficiency	AVG. 45%
Peak gain	4.6dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	15.6 × 13 × 130mm
Form factor	Rubber
Mounting type	Terminal
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	200mm
Operation temperature	–40°C to +85°C



YECT001W1DM

4G terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	35%–75%
Peak gain	2.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø9 × 54.9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP65
Operation temperature	–40°C to +85°C



YECT001W1CM

4G terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	30%–70%
Peak gain	3.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle SMA male
IP rating	IP53
Operation temperature	–40°C to +85°C



YECT001W1WM

4G terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	50% AVG.
Peak gain	3.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle SMA male
IP rating	IP54
Operation temperature	–40°C to +85°C



YECT003W1A

4G terminal mount rubber monopole external antenna
Compatible with Japan market

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz; 1450–2690 MHz; 3300–3800 MHz
Efficiency	25%–80%
Peak gain	3.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø12.4 × 50.8 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP67
Operation temperature	–40°C to +85°C



YECT011W1AM

4G terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	20%–70%
Peak gain	4.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector Type	SMA male
IP Rating	IP67
Operation temperature	–40°C to +85°C



YECT012W1AM

4G terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	52% AVG.
Peak gain	3.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA Male
Operation temperature	–40°C to +85°C



YECT009W1AM

4G terminal mount rubber monopole external antenna
Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	600–960 MHz, 1710–2690 MHz
Efficiency	20%–65%
Peak gain	2.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø10.22 × 69.5 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YE0013CA

4G terminal mount rubber monopole external antenna
Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	698–2700 MHz
Efficiency	45%–95%
Peak gain	4.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø10.2 × 115.4 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP66
Operation temperature	–40°C to +85°C



YCN001AA

4G terminal mount rubber monopole external antenna
Compatible with Japan market

Compliant
RoHS

Electrical data

Frequency range	698–960 MHz, 1560–1610 MHz, 1710–2700 MHz
Efficiency	48% AVG.
Peak gain	0 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Φ13 × 144 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP66
Operation temperature	–40°C to +85°C



YECT007AA

4G pole mount fiberglass dipole external antenna

Compliant
RoHS & REACH

Electrical data

Frequency range	698–2690 MHz
Efficiency	40%–95%
Peak gain	1.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Φ20 × 300 mm
Form factor	Fiberglass
Mounting type	Pole
Connector type	N type male
IP rating	IP65
Operation temperature	–40°C to +85°C



YE0010AA

4G adhesive mount low profile dipole external antenna
Compatible with Japan market

Compliant
RoHS

Electrical data

Frequency range	698–2700 MHz
Efficiency	30%–80%
Peak gain	2.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	152 × 18 × 11.1 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YECA000M1A

4G adhesive mount low profile monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698-960 MHz 1710-2690 MHz
Efficiency	36% AVG.
Peak gain	2.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø99.98 × 17.46 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	ALSR100
Cable length	1460 mm
IP rating	IP68
IK rating	IK10
Operation temperature	-40°C to +85°C



YECA000J1AM

4G adhesive mount low profile monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698-960 MHz, 1710-2690 MHz
Efficiency	35%-80%
Peak gain	4.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	60 × 16 × 6.3 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	213 mm
Operation temperature	-40°C to +85°C



YECW000N1A

4G screw mount low profile PIFA external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	450-470 MHz, 698-960 MHz, 1710-2690 MHz
Efficiency	20%-60%
Peak gain	3.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	150 × 50 × 36.5 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	ALSR100
Cable length	2000 mm
Operation temperature	-40°C to +85°C



YECW058L1BM

4G screw mount low profile dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	790–960 MHz, 1710–2690 MHz
Efficiency	50% AVG.
Peak gain	7.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	223.18 × 74.09 × 76.50 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1500 mm
Operation temperature	–40°C to +85°C



YECW058L1CM

4G screw mount low profile dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	450–470 MHz, 790–960 MHz, 1710–2690 MHz
Efficiency	50% AVG.
Peak gain	7.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	223.18 × 74.09 × 76.50 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1500 mm
Operation temperature	–40°C to +85°C



YECM002L1AH

4G magnetic mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	37% - 65%
Peak gain	4.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 82.2 mm
Form factor	Whip
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YECA002L1AH

4G adhesive mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698– 960 MHz, 1710 – 2690 MHz
Efficiency	37% – 65%
Peak gain	4.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 83.2 mm
Form factor	Whip
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEMN105J1AM

4G screw mount low profile monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	50% AVG.
Peak gain	5.0 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø46 × 16 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	300 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEMN117L1B

4G screw mount low profile monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410–470 MHz, 698–2690 MHz
Efficiency	30%–70%
Peak gain	4.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø108 × 45 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP67 & IP69K
IK rating	IK09
Operation temperature	–40°C to +85°C



YECN001L1A

4G screw mount stubby IFA external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	450–470 MHz, 698–960 MHz, 1710–2690 MHz
Efficiency	22%–64%
Peak gain	2.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø40.6 × 104 mm
Form factor	Stubby
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YE0006AA

4G magnetic mount whip monopole external antenna
Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	25%–60%
Peak gain	4.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 318 mm
Form factor	Whip
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174
Cable length	1500 mm
IP rating	IP65
Operation temperature	–40°C to +85°C



YECM000M5AH

4G adhesive & magnetic & screw mount low profile dipole external antenna

Compliant

RoHS & REACH&POPS

Frequency range

Frequency range	450–470 MHz, 698–960 MHz, 1710–2690 MHz
Efficiency	38%–65%
Peak gain	4.4dBi
Radiation pattern	omni-directional
Polarization	Linear
Polarization	Linear

Mechanical data

Dimensions	109.28 × 89 × 25.8mm
Form factor	Low profile
Mounting type	Adhesive & Magnetic & Screw
Connector type	Right angle Fakra female code D
Cable type	ALSR100
Cable length	1520mm
IP rating	IP68
Operation temperature	–40°C to +85°C

EXTERNAL

Wi-Fi antennas



YEBT001W1AM



YEBA000J1AM



YEBA001L1AH



YEBT001WFAM



YEBT001WFBM



YEBT010W1AM





YEBT001WFBM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	35%–70%
Peak gain	4.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø9 × 54.9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
IP rating	IP65
Operation temperature	–40°C to +85°C



YEBT001WFXM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	60% AVG.
Peak gain	4.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø9 × 54.9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
IP rating	IP65
Operation temperature	–40°C to +85°C



YEBT062W1AM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5850–5925 MHz, 5925–7125 MHz
Efficiency	50% AVG.
Peak gain	4.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP54
Operation temperature	–40°C to +85°C



YEBT001WFAM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	30%–65%
Peak gain	2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle RP SMA male
IP rating	IP54
Operation temperature	–40°C to +85°C



YEBT001WFWM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	50% AVG.
Peak gain	2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle RP SMA male
IP rating	IP54
Operation temperature	–40°C to +85°C



YEBT010W1AM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	38%–65%
Peak gain	4.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø10.22 × 69.5 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
Operation temperature	–40°C to +85°C



YEBT001W1AM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	45%–70%
Peak gain	4.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
IP rating	IP67
Operation temperature	–40°C to +85°C



YEBT002W1AM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	45%–75%
Peak gain	4.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
Operation temperature	–40°C to +85°C



YEBT002W1BM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	60% AVG.
Peak gain	4.8 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YEBT064W1AM

Wi-Fi terminal mount rubber dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	50% AVG.
Peak gain	4.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP67
Operation temperature	–40°C to +85°C



YEBA000J1AM

Wi-Fi adhesive mount low profile dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500MHz, 5150–5850MHz, 5925–7125 MHz
Efficiency	45%–65%
Peak gain	2.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	60 × 16 × 6.3 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	209 mm
Operation temperature	–40°C to +85°C



YEBT002E3AM

Wi-Fi terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	37%–64%
Peak gain	2.8dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	15.6 × 13 × 130mm
Form factor	Rubber
Mounting type	Terminal
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100mm
Operation temperature	–40°C to +85°C



YEBA001L1AH

Wi-Fi adhesive mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	30%–65%
Peak gain	4.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 83.2 mm
Form factor	Whip
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEBM001L1AH

Wi-Fi magnetic mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	30%–65%
Peak gain	4.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 82.2 mm
Form factor	Whip
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174LL
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEBT002W7AM

Wi-Fi terminal mount fiberglass dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400-2500MHz
Efficiency	0.73
Peak gain	4.3dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 25.5 × 300mm
Form factor	Fiberglass
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	–40°C to +85°C



YEVT001W7AM

V2X/DSRC terminal mount fiberglass
array external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	5850-5925MHz
Efficiency	59.5%~65.1%
Peak gain	7.1dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 25.5 × 600mm
Form factor	Fiberglass
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	-40°C to +85°C

EXTERNAL

Combo antennas

YEMA206J1AM



YEMD301L1A



YEMN210J1AH



YEMN926J1A



YEMN016AA



YEMA013AA



YEMA300QXA



YEMX425J1A





YEMN205J1AM

WiFi 2in1 screw mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range	2400–2500 MHz; 5150–5850 MHz
Efficiency	AVG. 55%
Peak gain	4.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø46 × 16 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	300mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YEMA206J1AM

4G & GNSS L1 2in1 adhesive mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range	4G × 1: 698–960 MHz; 1710–2690 MHz GNSS L1 × 1: 1559–1606 MHz
Efficiency	4G × 1: 65% AVG. GNSS L1 × 1: 60% AVG.
Peak gain	4G × 1: 7.0 dBi GNSS L1 × 1: 4.4 dBi
Radiation pattern	4G × 1: omni-directional GNSS L1 × 1: Directional
Polarization	4G × 1: Linear GNSS L1 × 1: RHCP
LNA gain	16 ± 3 dB

Mechanical data

Dimensions	Ø82 × 18.2 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	ALS302 & RG174
Cable length	300 mm & 300 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEMA004AA

4G & Wi-Fi 2in1 screw mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range	4G × 1: 698–960 MHz, 1710–2690 MHz Wi-Fi × 1: 2400–2500 MHz
Efficiency	4G × 1: 25%–50% Wi-Fi × 1: 35%–45%
Peak gain	4G × 1: 2.8 dBi Wi-Fi × 1: 2.6 dBi
Radiation pattern	4G × 1: omni-directional Wi-Fi × 1: omni-directional
Polarization	4G × 1: Linear Wi-Fi × 1: Linear

Mechanical data

Dimensions	Ø81 × 14.5 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	900 mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YEMN210J1AH

5G & Wi-Fi 2in1 screw mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	5G × 1: 600–960 MHz & 1400–6000 MHz Wi-Fi × 1: 2400–2500 MHz
Efficiency	5G × 1: 20%–80% Wi-Fi × 1: 53–62%
Peak gain	5G × 1: 5.9 dBi Wi-Fi × 1: 4.4 dBi
Radiation pattern	5G × 1: omni-directional Wi-Fi × 1: omni-directional
Polarization	5G × 1: Linear Wi-Fi × 1: Linear

Mechanical data

Dimensions	Ø40.6 × 104 mm
Form factor	Stubby
Mounting type	Screw
Connector type	SMA male
Cable type	RG174LL
Cable length	300 mm
IP rating	IP67 & IP69K
IK rating	IK10
Operation temperature	–40°C to +85°C



YEMN311J1AH

5G & GNSS L1 3in1 screw & adhesive mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range

5G × 2: 600–960 MHz, 1710–2690 MHz, 3300–6000 MHz

GNSS × 1: 1565–1606 MHz

Efficiency

5G × 2: 55% AVG.

GNSS × 1: 55% AVG.

Peak gain

5G × 2: 5.8 dBi

GNSS × 1: 5.3 dBi

Radiation pattern

5G × 2: omni-directional

GNSS × 1: omni-directional

Polarization

5G × 2: Linear

GNSS × 1: Linear

LNA gain

17 ±3 dB

Mechanical data

Dimensions

Ø54 × 91.8 mm

Form factor

Stubby

Mounting type

Screw & Adhesive

Connector type

SMA male

Cable type

RG174

Cable length

300 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMN312J1AH

5G & Wi-Fi & GNSS L1 3in1 screw & adhesive mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

5G × 1: 617–960 MHz, 1420–2690 MHz, 3300–6000 MHz

Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz

GNSS × 1: 1565–1606 MHz

Efficiency

5G × 1: 60% AVG.

Wi-Fi × 1: 60% AVG.

GNSS × 1: 52% AVG.

Peak gain

5G × 1: 7.3 dBi

Wi-Fi × 1: 7.9 dBi

GNSS × 1: 2.62 dBi

Radiation pattern

5G × 1: omni-directional

Wi-Fi × 1: omni-directional

GNSS × 1: Directional

Polarization

5G × 1: Linear

Wi-Fi × 1: Linear

GNSS × 1: RHCP

LNA gain

17 ±3 dB

Mechanical data

Dimensions

Ø54 × 91.8 mm

Form factor

Stubby

Mounting type

Screw & Adhesive

Connector type

SMA male

Cable type

RG174

Cable length

300 mm

IP rating

IP66

Operation temperature

–40°C to +85°C



YEMX223J1A

5G 2in1 multiple mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410–470 MHz, 617–960 MHz, 1420–1520 MHz, 1710–2690 MHz, 3300–3800 MHz, 4000–6000 MHz
Efficiency	50% AVG.
Peak gain	5.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	186 × 176 × 100.5 mm
Form factor	Low profile
Mounting type	Multiple
Connector type	SMA male
Cable type	ALSR200
Cable length	450 mm
IP rating	IP67
IK rating	IK09
Operation temperature	–40°C to +85°C



YEMA200L1AH

4G 2in1 adhesive mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	50% AVG.
Peak gain	3.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	143.73 × 51.33 × 15 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male & SMA male
Cable type	RG174LL & RG174LL
Cable length	1028mm & 1028 mm
IP rating	IP68
Operation temperature	–40°C to +85°C



YEMA300QXA

4G & Wi-Fi & GNSS L1 3in1 adhesive mount
combo external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	4G × 1: 698–960 MHz, 1710–2690 MHz Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz GNSS × 1: 1559–1606MHz
Efficiency	4G × 1: 25%–60% Wi-Fi × 1: 47%–53% GNSS × 1: 50%–75%
Peak gain	4G × 1: 4.1 dBi Wi-Fi × 1: 2.7 dBi GNSS × 1: 2.4 dBi
Radiation pattern	4G × 1: omni-directional Wi-Fi × 1: omni-directional GNSS × 1: Directional
Polarization	4G × 1: Linear Wi-Fi × 1: Linear GNSS × 1: RHCP
LNA gain	18 ± 3 dB

Mechanical data

Dimensions	143.73 × 51.33 × 15 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male & RP SMA male
Cable type	RG174LL & RG174
Cable length	1028 mm
IP rating	IP68
Operation temperature	–40°C to +85°C



YEMD301L1A

4G & GNSS L1 3in1 multiple mount combo
external antenna

Compliant

RoHS & REACH & POPS & CE

Electrical data

Frequency range	4G × 2: 698–960 MHz, 1710–2690 MHz GNSS × 1: 1565–1606 MHz
Efficiency	4G × 2: 40%–70% GNSS × 1: 76%–79%
Peak gain	4G × 2: 5.5 dBi GNSS × 1: 2.18 dBi
Radiation pattern	4G × 2: omni-directional GNSS × 1: Directional
Polarization	4G × 2: Linear GNSS × 1: RHCP
LNA gain	18 ± 3 dB

Mechanical data

Dimensions	109.28 × 89 × 25.8 mm
Form factor	Low profile
Mounting type	Multiple
Connector type	SMA male
Cable type	ALS302 & RG174
Cable length	1025 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEMD302L1A

4G & Wi-Fi & GNSS L1 3in1 multiple mount combo external antenna

Compliant

RoHS & REACH & POPS & CE

Electrical data

Frequency range

4G × 1: 698–960 MHz, 1710–2690 MHz
Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz

Efficiency

4G × 1: 30%–75%

Wi-Fi × 1: 33%–58%

GNSS × 1: 76%–79%

Peak gain

4G × 1: 5.1 dBi

Wi-Fi × 1: 5.8 dBi

GNSS × 1: 2.18 dBi

Radiation pattern

4G × 1: omni-directional

Wi-Fi × 1: omni-directional

GNSS × 1: Directional

Polarization

4G × 1: Linear

Wi-Fi × 1: Linear

GNSS × 1: RHCP

LNA gain

18 ± 3 dB

Mechanical data

Dimensions

109.28 × 89 × 25.8 mm

Form factor

Low profile

Mounting type

Multiple

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

1025 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMD301L1B

4G & GNSS L1 3in1 multiple mount combo external antenna

Compliant

RoHS & REACH & POPS & CE

Electrical data

Frequency range

4G × 2: 698–960 MHz, 1710–2690 MHz

GNSS × 1: 1565–1606 MHz

Efficiency

4G × 2: 40%–70%

GNSS × 1: 76%–79%

Peak gain

4G × 2: 5.5 dBi

GNSS × 1: 2.18 dBi

Radiation pattern

4G × 2: omni-directional

GNSS × 1: Directional

Polarization

4G × 2: Linear

GNSS × 1: RHCP

LNA gain

28 ± 3 dB

Mechanical data

Dimensions

109.28 × 89 × 25.8 mm

Form factor

Low profile

Mounting type

Multiple

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

1025 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMD302L1B

4G & Wi-Fi & GNSS L1 3in1 multiple mount combo external antenna

Compliant

RoHS & REACH & POPS & CE

Electrical data

Frequency range

4G × 1: 698–960 MHz, 1710–2690 MHz
Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
GNSS × 1: 1565–1606 MHz

Efficiency

4G × 1: 30%–75%
Wi-Fi × 1: 33%–58%
GNSS × 1: 76%–79%

Peak gain

4G × 1: 5.1 dBi
Wi-Fi × 1: 5.8 dBi
GNSS × 1: 2.18 dBi

Radiation pattern

4G × 1: omni-directional
Wi-Fi × 1: omni-directional
GNSS × 1: Directional

Polarization

4G × 1: Linear
Wi-Fi × 1: Linear
GNSS × 1: RHCP

LNA Gain

28 ± 3 dB

Mechanical data

Dimensions

109.28 × 89 × 25.8 mm

Form factor

Low profile

Mounting type

Multiple

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

1025 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMA301J1AM

4G & GNSS L1 3in1 adhesive mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range

4G × 2: 698–960 MHz, 1710–2690 MHz
GNSS L1 × 1: 1559–1606 MHz

Efficiency

4G × 2: 60% AVG.
GNSS L1 × 1: 60% AVG.

Peak gain

4G × 2: 7.0 dBi
GNSS L1 × 1: 4.4 dBi

Radiation pattern

4G × 2: omni-directional
GNSS L1 × 1: Directional

Polarization

4G × 2: Linear
GNSS L1 × 1: RHCP

LNA gain

16 ± 3 dB

Mechanical data

Dimensions

Ø82 × 18.2 mm

Form factor

Low profile

Mounting type

Adhesive

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

300 mm & 300 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMN302Q1A

4G & GNSS L1 3in1 screw mount combo external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	4G × 2: 698–960 MHz, 1710–2690 MHz GNSS × 1: 1565–1606 MHz
Efficiency	4G × 2: 30%–55% GNSS × 1: 66% AVG.
Peak gain	4G × 2: 3.3 dBi GNSS × 1: 2.57 dBi
Radiation pattern	4G × 2: omni-directional GNSS × 1: Directional
Polarization	4G × 2: Linear GNSS × 1: RHCP
LNA gain	18 ± 3 dB

Mechanical data

Dimensions	Ø81.4 × 16.5 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	ALSR100 & RG174
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YB0014AA

4G & GNSS L1 3in1 screw mount combo external antenna
Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	4G × 2: 698–960 MHz, 1710–2690 MHz GNSS × 1: 1559–1586 MHz
Efficiency	4G × 2: 10%–20% GNSS × 1: 36%–44%
Peak gain	4G × 2: –2.2 dBi GNSS × 1: 1.75dBi
Radiation pattern	4G × 2: omni-directional GNSS × 1: Directional
Polarization	4G × 2: Linear GNSS × 1: RHCP
LNA gain	22 ± 3 dB

Mechanical data

Dimensions	Ø81×14.5 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YEMN308L1AM

4G & GNSS L1 3in1 screw mount
combo external antenna

Compliant

RoHS

Electrical data

Frequency range

4G × 2: 698–960 MHz, 1710–2690 MHz

Efficiency

GNSS L1 × 1: 1565–1606 MHz

4G × 2: 30%–56%

GNSS L1 × 1: 0.48

Peak gain

4G × 2: 3.1dBi

GNSS L1 × 1: 1.32dBi

Radiation pattern

4G × 2: omni-directional

GNSS L1 × 1: Directional

Polarization

4G × 2: Linear

GNSS L1 × 1: RHCP

LNA gain

18 ±3 dB

Mechanical data

Dimensions

Ø 81 × 15.5 mm

Form factor

Low profile

Mounting type

Screw & Adhesive

Connector type

SMA male

Cable type

RG174

Cable length

300 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMN308L1BM

5G & Wi-Fi & GNSS L1 3in1 screw & adhesive
mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

5G × 1: 698–960 MHz, 1420–2690 MHz, 3300–6000 MHz

Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz

GNSS L1 × 1: 1565–1606 MHz

Efficiency

5G × 1: 45% AVG.

Wi-Fi × 1: 40% AVG.

GNSS L1 × 1: 50% AVG.

Peak gain

5G × 1: 5.4 dBi

Wi-Fi × 1: 4.2 dBi

GNSS L1 × 1: 1.32 dBi

Radiation pattern

4G × 2: omni-directional

GNSS L1 × 1: Directional

Polarization

5G × 1: Linear

Wi-Fi × 1: Linear

GNSS L1 × 1: RHCP

LNA gain

18 ±3 dB

Mechanical data

Dimensions

Ø 81 × 15.5 mm

Form factor

Low profile

Mounting type

Screw & Adhesive

Connector type

SMA male

Cable type

RG174

Cable length

1000 mm

IP rating

IP67

Operation temperature

–20°C to +70°C



YEMN310L1AM

4G & GNSS L1 3in1 screw mount
combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

4G × 2: 698–960 MHz, 1710–2690 MHz

Efficiency

GNSS L1 × 1: 1565–1606 MHz

4G × 2: AVG. 45%

GNSS L1 × 1: 26.7%~62.5%

Peak gain

4G × 2: 6.3dBi

GNSS L1 × 1: 1.57dBi

Radiation pattern

4G × 2: omni-directional

GNSS L1 × 1: Directional

Polarization

4G × 2: Linear

GNSS L1 × 1: RHCP

LNA gain

18 ± 3 dB

Mechanical data

Dimensions

89.3 × 86.3 × 35.4 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

300 mm & 300 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMX425J1A

5G 4in1 multiple mount combo
external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

410–470 MHz, 617–2690 MHz, 3300–6000 MHz

Efficiency

50% AVG.

Peak gain

5.3 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

186 × 176 × 150 mm

Form factor

Low profile

Mounting type

Multiple

Connector type

SMA male

Cable type

ALSR200

Cable length

450 mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YEMN017AA

5G & GNSS L1 & L5 5in1 screw mount combo external antenna

Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range

5G × 2: 600–960 MHz, 1400–6000 MHz; 5G × 2: 1400–6000 MHz

Efficiency

GNSS × 1: 1164–1189 MHz, 1559–1606 MHz

5G × 2: 50% AVG.; 5G × 2: 30%–70%

Peak gain

GNSS × 1: L1: 40%–42%, L5: 45%–47%

5G × 2: 5 dBi; 5G × 2: 4.9 dBi

Radiation pattern

GNSS × 1: L1: –1.2 dBi, L5: 0 dBi

5G × 2: omni-directional; 5G × 2: omni-directional

Polarization

GNSS × 1: Directional

5G × 2: Linear; 5G × 2: Linear

LNA gain

GNSS × 1: RHCP

28 dB

Mechanical data

Dimensions

Ø103.5 × 42.5 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

RG405 & RG174

Cable length

300 mm

IP rating

IP67 & IP69K

IK rating

IK09

Operation temperature

–40°C to +85°C



YEMN400J1AH

5G 4in1 screw mount combo external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range

5G × 2: 600–6000 MHz, 5G × 2: 1400–6000 MHz

Efficiency

5G × 2: 50% AVG.; 5G × 2: 30%–70%

Peak gain

5G × 2: 5.0 dBi, 5G × 2: 4.9 dBi

Radiation pattern

5G × 2: omni-directional, 5G × 2: omni-directional

Polarization

5G × 2: Linear, 5G × 2: Linear

Mechanical data

Dimensions

Ø103.5 × 42.5 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

RG405

Cable length

300 mm

IP rating

IP67 & IP69K

IK rating

IK09

Operation temperature

–40°C to +85°C



YEMN301J1AH

5G & GNSS L1 & L5 3in1 screw mount combo external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range

5G × 2: 600-6000 MHz

GNSS L1 & L5 × 1: 1164-1189 MHz, 1559-1606 MHz

Efficiency

5G × 2: 50% AVG.

GNSS L1 & L5 × 1: L1: 40%-42%, L5: 45%-47%

Peak gain

5G × 2: 5.0 dBi

GNSS L1 & L5 × 1: L1: -1.2 dBi, L5: 0 dBi

Radiation pattern

5G × 2: omni-directional

GNSS L1 & L5 × 1: L1: -1.2 dBi, L5: 0 dBi

Polarization

5G × 2: Linear

GNSS L1 & L5 × 1: RHCP

LNA gain

28 dB

Mechanical data

Dimensions

Ø103.5 × 42.5 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

RG405 & RG174

Cable length

300 mm & 300 mm

IP rating

IP67 & IP69K

IK rating

IK09

Operation temperature

-40°C to +85°C



YEMN016AA

5G & GNSS L1 & L5 5in1 screw mount combo external antenna

Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range

5G × 2: 600-960 MHz, 1400-6000 MHz; 5G × 2: 1400-6000 MHz

GNSS × 1: 1164-1189 MHz, 1559-1606 MHz

Efficiency

5G × 2: 20%-70%; 5G × 2: 20%-60%

GNSS × 1: L1: 50%-52%, L5: 75%-78%

Peak gain

5G × 2: 5.9 dBi; 5G × 2: 4.7 dBi

GNSS × 1: L1: 2.7 dBi, L5: 4.3 dBi

Radiation pattern

5G × 2: omni-directional; 5G × 2: omni-directional

GNSS × 1: Directional

Polarization

5G × 2: Linear, 5G × 2: Linear, GNSS × 1: RHCP

LNA gain

28 dB

Mechanical data

Dimensions

204.4 × 86.7 × 32 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length


300 mm

IP rating

IP67 & IP69K

Operation temperature

-40°C to +85°C



YEMM701K1AH

5G & GNSS L1 7in1 magnetic mount
combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

5G × 4: 600–960 MHz, 1400–6000 MHz

5G × 2: 1400–6000 MHz

GNSS L1 × 1: 1565–1606 MHz

Efficiency

5G × 4: AVG. 35%

5G × 2: AVG. 30%

GNSS L1 × 1: 40%–45%

Peak gain

5G × 4: 2.7dBi

5G × 2: 2.1dBi

GNSS L1 × 1: 1.94dBi

Radiation pattern

5G × 4: omni-directional

5G × 2: omni-directional

GNSS L1 × 1: Directional

Polarization

5G × 4: Linear

5G × 2: Linear

GNSS L1 × 1: RHCP

LNA gain

18 ±3dB

Mechanical data

Dimensions

133 × 73 × 19.1 mm

Form factor

Low profile

Mounting type

Magnetic

Connector type

SMA male

Cable type

RG174LL & RG174

Cable length

1000mm & 1000mm

IP rating

IP67

Operation temperature

–40°C to +85°C



YB0027AA

5G & GNSS L1 & L5 9in1 screw mount combo
external antenna

Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH

Electrical data

Frequency range

5G × 4: 600–960 MHz, 1400–6000 MHz; 5G × 4: 1400–6000 MHz

GNSS × 1: 1164–1189 MHz, 1559–1606 MHz

Efficiency

5G × 4: 25%–60%; 5G × 4: 30%–70%

GNSS × 1: L1: 45%–66%, L5: 80%–85%

Peak gain

5G × 4: 4.9 dBi; 5G × 4: 4.1 dBi

GNSS × 1: L1: 3.8 dBi, L5: 4.7 dBi

Radiation pattern

5G × 4: omni-directional; 5G × 4: omni-directional

GNSS × 1: Directional

Polarization

5G × 4: Linear; 5G × 4: Linear

GNSS × 1: RHCP

LNA gain

22 ± 3 dB

Mechanical data

Dimensions

Ø162 × 56 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

300 mm

IP rating

IP67 & IP69K

IK rating

IK09

Operation temperature

–40°C to +85°C



YEMN701J1AH

5G & GNSS L1 & L5 7in1 screw mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

5G × 4: 600-6000MHz; 5G × 2: 1400-6000MHz

Efficiency

GNSS × 1: 1164-1189MHz, 1559-1606MHz

5G × 4: 25%-60%; 5G × 2: 30%-70%

GNSS × 1: L1:45%-66%, L5:80%-85%

Peak gain

5G × 4: 4.9 dBi; 5G × 2: 4.1 dBi

GNSS × 1: L1: 3.8dBi, L5: 4.7dBi

Radiation pattern

5G × 4: omni-directional; 5G × 2: omni-directional

GNSS × 1: Directional

Polarization

5G × 4: Linear; 5G × 2: Linear

GNSS × 1: RHCP

LNA gain

28 dB

Mechanical data

Dimensions

Ø162 × 56 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

300 mm

IP rating

IP67 & IP69K

IK Rating

IK 09

Operation temperature

-40°C to +85°C



YEMN926J1A

5G & GNSS L1 & L5 9in1 screw mount combo external antenna

Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range

5G × 4: 600-960 MHz, 1400-6000 MHz; 5G × 4: 1400-6000 MHz

GNSS × 1: 1164-1189 MHz, 1559-1606 MHz

Efficiency

5G × 4: 46% AVG.; 5G × 4: 30%-60%

GNSS × 1: L1: 45%-66%, L5: 80%-85%

Peak gain

5G × 4: 4.3 dBi; 5G × 4: 5.4 dBi

GNSS × 1: L1: 3.8 dBi, L5: 4.7 dBi

Radiation pattern

5G × 4: omni-directional; 5G × 4: omni-directional

GNSS × 1: Directional

Polarization

5G × 4: Linear; 5G × 4: Linear

GNSS × 1: RHCP

LNA gain

22 ± 3 dB

Mechanical data

Dimensions

Ø167 × 57 mm

Form factor

Low profile

Mounting type

Screw

Connector type

SMA male

Cable type

ALS302 & RG174

Cable length

300 mm

IP rating


IP67 & IP69K

IK rating

IK09

Operation temperature

-40°C to +85°C



YEMA013AA

5G & GNSS L1 & L5 9in1 adhesive mount
combo external antenna
Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	5G × 4: 600–960 MHz, 1400–6000 MHz; 5G × 4: 1400–6000 MHz GNSS × 1: 1166–1186 MHz, 1559–1606 MHz
Efficiency	5G × 4: 30%–75%; 5G × 4: 30%–70% GNSS × 1: L1: 50%–53%, L5: 55%–60%
Peak gain	5G × 4: 5.6 dBi; 5G × 4: 6.3 dBi GNSS × 1: L1: 4.2 dBi, L5: 2.8 dBi
Radiation pattern	5G × 4: omni-directional; 5G × 4: omni-directional GNSS × 1: Directional
Polarization	5G × 4: Linear; 5G × 4: Linear GNSS × 1: RHCP
LNA gain	28 dB

Mechanical data

Dimensions	264.6 × 161.2 × 30.6 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	ALSR200 & RG174
Cable length	300 mm
IP rating	IP67 & IP69K
IK rating	IK09
Operation temperature	–40°C to +85°C

EXTERNAL

GNSS antennas



YEGB001Q1A



YEGT000W8A



YEGN103W8A



YEGD006U1A



YEGT003W1AM



YEGT010W1AM



YEGT001W1AM



YETN001L1A





YEGB000Q1C

GNSS L1 adhesive & magnetic mount
low profile active external antenna
Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1565–1606 MHz
Efficiency	70%–73%
Peak gain	1.7 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 ± 3 dB

Mechanical data

Dimensions	46 × 36 × 15.8 mm
Form factor	Low profile
Mounting type	Adhesive & magnetic
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGA001Q1AM

GNSS L1 adhesive mount low profile
active external antenna

Compliant

RoHS

Electrical data

Frequency range	1559–1606 MHz
Efficiency	42.1%–45.3%
Peak gain	–0.34dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	21 ± 3dB

Mechanical data

Dimensions	55.6 × 50.3 × 18 mm
Form factor	Low profile
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YEGM001Q1AM

GNSS L1 magnetic mount low profile
active external antenna

Compliant

RoHS

Electrical data

Frequency range	1559–1606 MHz
Efficiency	42.1%–45.3%
Peak gain	–0.34dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	21 ± 3dB

Mechanical data

Dimensions	55.6 × 50.3 × 18 mm
Form factor	Low profile
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP66
Operation temperature	–40°C to +85°C



YEGB000Q1A

GNSS L1 & L5 adhesive & magnetic mount
low profile active external antenna
Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 40%–70%, L5: 50%–60%
Peak gain	L1: 3.4 dBi, L5: 1.4 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	62 × 56 × 23 mm
Form factor	Low profile
Mounting type	Adhesive & magnetic
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP68
IK rating	IK09
Operation temperature	–40°C to +85°C



YEGN000Q1A

GNSS L1 & L5 bracket mount low profile
active external antenna
Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 40%–70%, L5: 50%–60%
Peak gain	L1: 3.4 dBi, L5: 1.4 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	62 × 56 × 23 mm
Form factor	Low profile
Mounting type	Bracket
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP68
IK rating	IK09
Operation temperature	–40°C to +85°C



YEGB001Q1A

GNSS L1 & L5 adhesive & magnetic mount
low profile active external antenna
Compatible with ECE-R118 cables
under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1165–1189 MHz, 1559–1606 MHz
Efficiency	L1: 32%–52%, L5: 50%–52%
Peak gain	L1: 1.2 dBi, L5: 1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	55.2 × 48 × 20.5 mm
Form factor	Low profile
Mounting type	Adhesive & magnetic
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGN001Q1A

GNSS L1 & L5 bracket mount low profile active external antenna
Compatible with ECE-R118 cables under demand

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 32%–52%, L5: 50%–52%
Peak gain	L1: 1.2 dBi, L5: 1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	55.2 × 48 × 20.5 mm
Form factor	Low profile
Mounting type	Bracket
Connector type	SMA male
Cable type	RG174
Cable length	3000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGD006U1A

GNSS full band adhesive & magnetic & screw mount low profile active external antenna

Compliant

RoHS & REACH & POPS & CE

Electrical data

Frequency range	Lower band: 1164–1300 MHz; L-band: 1525–1559 MHz; Upper band: 1559–1606 MHz
Efficiency	Lower band: 63%; L-band: 51%; Upper band: 80%
Peak gain	Lower band: 3.27 dBi; L-band: 2.46 dBi; Upper band: 4.77 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA Gain	30 ± 4 dB

Mechanical data

Dimensions	109.28 × 89 × 25.8 mm
Form factor	Low profile
Mounting type	Adhesive & magnetic & screw
Connector type	SMA male
Cable type	RG174
Cable length	5055 mm
IP rating	IP68
Operation temperature	–40°C to +85°C



YEGN010L1AM

GNSS full band screw mount low profile active external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1164–1300 MHz, 1525–1606 MHz
Efficiency	65% AVG.
Peak gain	4.75 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	38 ± 4 dB

Mechanical data

Dimensions	89.3 × 86.3 × 35.4 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGT002W1AM

GNSS L1 terminal mount rubber passive external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	57%–62%
Peak gain	2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	52.6 × 18.6 × 9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	Right angle SMA male
IP rating	IP53
Operation temperature	–40°C to +85°C



YEGT003W1AM

GNSS L1 terminal mount rubber passive external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	52%–56%
Peak gain	1.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø9 × 54.9 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP65
Operation temperature	–40°C to +85°C



YEGT010W1AM

GNSS L1 magnetic mount rubber passive external antenna

Compliant

RoHS

Electrical data

Frequency range	1559–1606 MHz
Efficiency	75.5%–78.2%
Peak gain	3.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø10.22 × 69.5 mm
Form factor	Rubber
Mounting type	Magnetic
Connector type	SMA male
Operation temperature	–40°C to +85°C



YEGT001W1AM

GNSS L1 terminal mount rubber passive external antenna

Compliant

RoHS

Electrical data

Frequency range	1559–1606 MHz
Efficiency	70%–76%
Peak gain	2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø13 × 135 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YEGT000W8A

GNSS L1 & L5 screw mount low profile active external antenna

Compliant

RoHS

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 27%–36%, L5: 45%–48%
Peak gain	L1: –0.5 dBi, L5: –0.5 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	28 dB

Mechanical data

Dimensions	Ø65 × 45 mm
Form factor	Low profile
Mounting type	Screw
Connector type	TNC female
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGN103W8A

GNSS L1 & L2 & L5 & E6 & L-band magnetic mount low profile active external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1164–1300 MHz, 1525–1606 MHz
Efficiency	Lower band: 67%, L-band: 49%, Upper band: 77%
Peak gain	Lower band: 5.4 dBi, L-band: 3.3 dBi, Upper band: 5.5 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	40 ± 4 dB

Mechanical data

Dimensions	Ø146.4 × 71.43 mm
Form factor	Low profile
Mounting type	Magnetic
Connector type	SMA male
Cable Type	RG174
Cable Length	3000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YEGR001W8AH

GNSS L1 & L2 & L5 & E6 & L-band terminal mount low profile active external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	1164-1300 MHz, 1525-1606 MHz
Efficiency	L2/L5/E6/B3: 30%~67%, L1: 58%~76%
Peak gain	L2/L5/E6/B3: 5.4 dBi, L1: 5.5 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	40 ± 4 dB

Mechanical data

Dimensions	Ø146.4 × 71.43 mm
Form factor	Low profile
Mounting type	Terminal
Connector type	TNC female
IP rating	IP67
Operation temperature	-40°C to +85°C



YEGN002W8AH

GNSS full band screw mount low profile active external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1164-1300 MHz, 1525-1606 MHz
Efficiency	Lower Band: 62%; L-band: 69%; Upper Band: 89.8%
Peak gain	Lower Band: 4.5 dBi; L-band: 4.7 dBi; Upper Band: 6.1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	37 ± 4 dB

Mechanical data

Dimensions	Ø146.4 × 71.43 mm
Form factor	Low profile
Mounting type	Screw
Connector type	TNC female
IP rating	IP67
Operation temperature	-40°C to +85°C



YETNO10L1AM

NTN screw mount low profile passive external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	TX: 1626.5–1660.5 MHz RX: 1525–1559 MHz
Efficiency	75% AVG.
Peak gain	5.4 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	89.3 × 86.3 × 35.4 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	ALS302
Cable length	500 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YETNO01L1A

L-Band & GNSS L1 & Iridium screw mount low profile passive external antenna

Compliant

RoHS & REACH & CE

Electrical data

Frequency range	GNSS: 1559–1606 MHz L-Band: 1518–1559 MHz, 1626–1660 MHz, 1668–1675 MHz Iridium: 1616–1626 MHz
Efficiency	GNSS: 60%–65% L-Band: 45%–72% Iridium: 68%–70%
Peak gain	GNSS: 4.3 dBi L-Band: 4.2 dBi Iridium: 4.2 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	106.15 × 87.21 × 26.5 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	ALS302
Cable length	524 mm
IP rating	IP67 & IP69K
IK rating	IK09
Operation temperature	–40°C to +85°C

EXTERNAL

LPWA/ISM antennas



YENA001L1AH



YENT001W1AM





YENTO60W1AM

LPWA/ISM terminal mount rubber
monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	863–930 MHz
Efficiency	50% AVG.
Peak gain	1.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 9.4 × 34.7 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YENTO60W1BM

LPWA/ISM terminal mount rubber
monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	450–470 MHz
Efficiency	25% AVG.
Peak gain	–3.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 9.4 × 34.7 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YENTO02F3AM

LPWA/ISM terminal mount rubber
dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	860–930 MHz
Efficiency	AVG. 56.2%
Peak gain	1.9dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	15.6 × 13 × 130 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	150mm
Operation temperature	–40°C to +85°C



YENTO00W1AM

LPWA/ISM terminal mount rubber monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410-470 MHz
Efficiency	24%-83%
Peak gain	1.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
IP rating	IP67
Operation temperature	-40°C to +85°C



YENTO01W1AM

LPWA/ISM terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	410-470 MHz
Efficiency	57%~70%
Peak gain	1.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	-40°C to +85°C



YENTO02W1AM

LPWA/ISM terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	850-950 MHz
Efficiency	41-57%
Peak gain	1.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	RP SMA male
Operation temperature	-40°C to +85°C



YENT065W1BM

LPWA/ISM terminal mount rubber dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	850–950 MHz
Efficiency	55% AVG.
Peak gain	1.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YENT001W1WM

LPWA/ISM terminal mount rubber monopole external antenna

Compliant

RoHS

Electrical data

Frequency range	410–470 MHz
Efficiency	60% AVG.
Peak gain	1.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	135 × 15.6 × 13 mm
Form factor	Rubber
Mounting type	Terminal
Connector type	SMA male
Operation temperature	–40°C to +85°C



YENM001L1AH

LPWA/ISM magnetic mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	433–435 MHz, 450–470 MHz
Efficiency	35%–40%
Peak gain	3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 82.2 mm
Form factor	Whip
Mounting type	Magnetic
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YENA001L1AH

LPWA/ISM adhesive mount whip monopole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	433–435 MHz, 450–470 MHz
Efficiency	35%–40%
Peak gain	3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø30 × 83.2 mm
Form factor	Whip
Mounting type	Adhesive
Connector type	SMA male
Cable type	RG174
Cable length	1000 mm
IP rating	IP67
Operation temperature	–40°C to +85°C



YECW058L1AM

LPWA/ISM screw mount low profile dipole external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	400–470 MHz
Efficiency	55% AVG.
Peak gain	2.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	223.18 × 74.09 × 76.50 mm
Form factor	Low profile
Mounting type	Screw
Connector type	SMA male
Cable type	RG174
Cable length	1500 mm
Operation temperature	–40°C to +85°C



YENTO06W7AM

LPWA/ISM terminal mount fiberglass array external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	902–928MHz
Efficiency	0.677
Peak gain	3.8dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 25.5 × 600 mm
Form factor	Fiberglass
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	–40°C to +85°C



YENT005W7AM

LPWA/ISM terminal mount fiberglass
array external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	860-870 MHz
Efficiency	0.65
Peak gain	3.1dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Ø 25.5 × 600mm
Form factor	Fiberglass
Mounting type	Terminal
Connector type	N type male
IP rating	IP67
Operation temperature	-40°C to +85°C



YEMJ294JPAM

5G 2in1 screw mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	617–5950 MHz
Peak gain	6.5 dBi
Polarization	Linear

Mechanical data

Dimensions	Ø 256 × 18 mm
Form factor	Small cell
Mounting type	Screw
Connector type	4.3.10-female
Cable type	402 NM FJ
Cable length	300 mm
Operation temperature	–40°C to +60°C



YEMG493KPAM

5G 4in1 wall & pole mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	3300–4200 MHz
Peak gain	12 dBi
Polarization	±45°

Mechanical data

Dimensions	210 × 210 × 48 mm
Form factor	Small cell
Mounting type	Wall & Pole
Connector type	4.3.10-female
Cable type	402 NM FJ
Cable length	500 mm
IP rating	IP65
Operation temperature	–40°C to +60°C



YECJ095JPAM

5G screw mount Ceiling dipole external antenna

Compliant

RoHS

Electrical data

Frequency range	380–6000 MHz
Peak gain	5 dBi
Radiation pattern	omni-directional
Polarization	Vertical

Mechanical data

Dimensions	Ø 300 × 139 mm
Form factor	Ceiling
Mounting type	Screw
Connector type	4.3.10-female
Cable type	402 NM FJ
Cable length	300 mm
Operation temperature	–40 °C to +55 °C



YEMG298WBAM

Wi-Fi 2in1 pole mount combo external antenna

Compliant

RoHS

Electrical data

Frequency range

Wi-Fi × 1: 2400–2483 MHz

Wi-Fi × 1: 5150–5850 MHz

Peak gain

Wi-Fi × 1: 14 dBi

Wi-Fi × 1: 17 dBi

Polarization

Vertical & Horizontal

Mechanical data

Dimensions

270 × 270 × 43.41 mm

Form factor

Small cell

Mounting type

Pole

Connector type

N type female & N type female

Operation temperature

–40 °C to +65 °C



YEMG492WPAM

5G 4in1 wall & pole mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

1695–2690 MHz, 3300–4200 MHz

Peak gain

15.6 dBi

Polarization

±45°

Mechanical data

Dimensions

595 × 419 × 143 mm

Form factor

Small cell

Mounting type

Wall & Pole

Connector type

7/16DIN-female & 4.3.10-female

Operation temperature

–40 °C to +70 °C



YEMG496KPAM

5G 4in1 wall & pole mount combo external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

617–4200 MHz

Peak gain

8.2 dBi

Polarization

±45°

Mechanical data

Dimensions

595 × 419 × 143 mm

Form factor

Small cell

Mounting type

Wall & Pole

Connector type

4.3.10-female

Cable type

402 NM FJ

Cable length

500 mm

Operation temperature

–30 °C to +60 °C



YEME490WPAM

4G 4in1 pole mount combo
external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz
Peak gain	13 dBi
Polarization	±45°

Mechanical data

Dimensions	850 × 645 × 850 mm
Form factor	Small cell
Mounting type	Pole
Connector type	4.3.10-female
Operation temperature	-40 °C to +70 °C



YEME491WPAM

4G 4in1 pole mount combo
external antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1710–2690 MHz
Peak gain	16.5 dBi
Polarization	±45°

Mechanical data

Dimensions	774 × 400 × 400 mm
Form factor	Small cell
Mounting type	Pole
Connector type	4.3.10-female
Operation temperature	-40 °C to +70 °C

EMBEDDED

5G antennas



YC0018CA



YPCS001AA



YF0017FA



YFCA010AA




YFCA011AA



YF0020EA





YC0018CA

5G SMT mount PCB chip IFA
embedded antenna

EVB

YC0018CAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

617–960 MHz, 1420–1520 MHz, 1710–2690 MHz, 3300–4200 MHz,
4400–5000 MHz, 5150–5850 MHz

Efficiency

20%–75%

Peak gain

5.9 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 40 × 7 × 3 mm, EVB: 141 × 40.4 × 0.8 mm

Form factor

PCB chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YPCS001AA

5G SMT mount PCB chip monopole
embedded antenna

EVB

YPCS001AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

1427–5850 MHz

Efficiency

20%–65%

Peak gain

2.6 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 20 × 10 × 3 mm, EVB: 60 × 20 × 0.8 mm

Form factor

PCB chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YF0017FA

5G adhesive mount FPC + cable dipole
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

1500–6000 MHz

Efficiency

45%–75%

Peak gain

4.4 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

49 × 13 mm

Form factor

FPC + cable

Mounting type

Adhesive

Connector type

IPEX MHF4L

Cable type

RF1.13

Cable length

201 mm

Operation temperature

–40°C to +85°C



YF0017GA

5G adhesive mount FPC + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1100–6000 MHz
Efficiency	53% AVG.
Peak gain	6.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	49 × 13 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	201 mm
Operation temperature	–40°C to +85°C



YF0020EA

5G adhesive mount FPC + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	30%–90%
Peak gain	4.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	90.3 × 15.3 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	202 mm
Operation temperature	–40°C to +85°C



YFCA010AA

5G adhesive mount FPC + cable dipole embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	410–470 MHz; 698–960 MHz; 1400–6000 MHz
Efficiency	23%–68%
Peak gain	3.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	138.8 × 16.2 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	101 mm
Operation temperature	–40°C to +85°C



YP0009NA

5G adhesive mount PCB + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1100–6000 MHz
Efficiency	30%–80%
Peak gain	5.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	49 × 13 × 0.8 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	202 mm
Operation temperature	–40°C to +85°C



YP0009OA

5G adhesive mount PCB + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	30%–75%
Peak gain	5.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	78.5 × 14.2 × 0.8 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	202 mm
Operation temperature	–40°C to +85°C



YPCA006AA

5G adhesive mount PCB + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410–470 MHz; 698–960 MHz; 1400–6000 MHz
Efficiency	16%–75%
Peak gain	3.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	150 × 16.2 × 0.6 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	101 mm
Operation temperature	–40°C to +85°C



YFCA011AA

5G adhesive mount FPC + cable dipole
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

600–960 MHz, 1520–6000 MHz

Efficiency

20%–75%

Peak gain

7.5 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

120 × 47 mm

Form factor

FPC + cable

Mounting type

Adhesive

Connector type

IPEX MHF1

Cable type


RF1.37

Cable length

150 mm

Operation temperature

–40°C to +85°C



YFCP018WWA

5G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP018WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

617–960 MHz, 1420–1520 MHz, 1710–2690 MHz,
3300–4200 MHz, 4400–5000 MHz, 5150–5850 MHz

Efficiency

43% AVG.

Peak gain

2.9 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 40 × 7 × 3 mm, EVB: 141 × 40.4 mm

Form factor

PCB chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YFCP001WWA

5G SMT mount PCB chip monopole
embedded antenna
Compatible with Japan market

EVB

YFCP001WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

1427–5850 MHz

Efficiency

45% AVG.

Peak gain

2.7 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 20 × 10 × 3 mm, EVB: 60 × 20 mm

Form factor

PCB chip

Mounting type

SMT

Operation temperature

–40°C to +85°C

EMBEDDED

4G antennas



YC0003BA



YMCP001AA



YMCP002AA



YF0006PA



YF0003FA



YF0028AA




YC0002AA



YPCA004AA





YC0001CA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YC0001CAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2700 MHz
42% AVG.
2.7 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 35 × 8.5 × 3 mm, EVB: 121.4 × 65 × 1 mm
PCB chip
SMT
–40°C to +85°C



YC0002AA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YC0002AAEVB

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
30%–80%
3.5 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 42 × 10 × 3 mm, EVB: 131 × 60 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YC0002BA

4G SMT mount PCB chip IFA
embedded antenna

EVB

YC0002BAEVB

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
30%–75%
4.1 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 42 × 10 × 3 mm, EVB: 131 × 60 mm
PCB chip
SMT
–40°C to +85°C



YC0003BA

4G SMT Mount PCB chip IFA
embedded antenna

EVB

YC0003BAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
30%–60%
3.1 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 40 × 7 × 3 mm, EVB: 136.5 × 43 × 1 mm
PCB chip
SMT
–40°C to +85°C



YC0017DA

4G SMT mount PCB chip IFA
embedded antenna

EVB

YC0017DAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz, 3300–3800 MHz
25%–75%
3.1 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 25 × 7 × 3 mm, EVB: 140 × 36 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YPCP001AA

4G SMT mount PCB chip IFA
embedded antenna

EVB

YPCP001AAEVB

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–960 MHz, 1710–2690 MHz
20%–75%
3.1 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 36 × 9 × 3 mm, EVB: 110 × 45.5 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YPCP003AA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YPCP003AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

Efficiency

Peak gain

Radiation pattern

Polarization

698–960 MHz, 1695–2200 MHz, 2300–2700 MHz

50% AVG.

3.3 dBi

omni-directional

Linear

Mechanical data

Dimensions

Form factor

Mounting type


Operation temperature

Antenna: 28 × 8 × 3 mm, EVB: 130 × 36 mm

PCB chip

SMT

–40°C to +85°C



YPCP003BA

4G SMT mount PCB chip IFA
embedded antenna

EVB

YPCP003BAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

Efficiency

Peak gain

Radiation pattern

Polarization

698–960 MHz, 1695–2200 MHz, 2300–2700 MHz

46% AVG.

3.7 dBi

omni-directional

Linear

Mechanical data

Dimensions

Form factor

Mounting type


Operation temperature

Antenna: 28 × 8 × 3 mm, EVB: 130 × 36 mm

PCB chip

SMT

–40°C to +85°C



YC0017EA

4G SMT mount PCB chip IFA
embedded antenna

EVB

YC0017EAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

Efficiency

Peak gain

Radiation pattern

Polarization

698–960 MHz, 1710–2690 MHz, 3300–3800 MHz

20%–75%

3.1 dBi

omni-directional

Linear

Mechanical data

Dimensions

Form factor

Mounting type

Operation temperature

Antenna: 25 × 7 × 3 mm, EVB: 140 × 36 × 0.8 mm

PCB chip

SMT

–40°C to +85°C



YMCP001AA

4G screw mount sheet metal + holder PIFA embedded antenna
Compatible with Japan market

EVB

YMCP001AAEVBAA

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2700 MHz
48% AVG.
2.2 dBi
omni-directional
Linear

Mechanical data

Dimensions

Antenna: 43.19 × 12.73 × 8.15 mm

YMCP001AAEVBAA: 145 × 75 mm

Form factor


Sheet metal + holder

Mounting type

Screw

Operation temperature

–40°C to +85°C



YMCP002AA

4G SMT mount sheet metal PIFA embedded antenna

EVB

YMCP002AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–960 MHz, 1710–2690 MHz
40%–75%
3.9 dBi
omni-directional
Linear

Mechanical data

Dimensions

Antenna: 40 × 7.23 × 7.6 mm, EVB: 40 × 136.5 mm

Form factor

Sheet metal

Mounting type

SMT

Operation temperature

–40°C to +85°C



YFCA002HA

4G adhesive mount FPC + cable monopole embedded antenna
Compatible with Japan market

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
20%–75%
3.7 dBi
omni-directional
Linear

Mechanical data

Dimensions

30 × 20 mm

Form factor

FPC + cable

Mounting type

Adhesive

Connector type

IPEX MHF1

Cable type

RF1.13

Cable length

86.5 mm

Operation temperature

–40°C to +85°C



YF0006PA

4G adhesive mount FPC + cable monopole
embedded antenna
Compatible with Japan market

Compliant


RoHS & REACH

Electrical data

Frequency range	698–2700 MHz
Efficiency	52% AVG.
Peak gain	3.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	50 × 25 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	90 mm
Operation temperature	–40°C to +85°C



YF0003FA

4G adhesive mount FPC + cable monopole
embedded antenna

Compliant

RoHS

Electrical data

Frequency range	824–960 MHz, 1710–2690 MHz
Efficiency	25%–70%
Peak gain	3.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	62 × 19 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	150 mm
Operation temperature	–40°C to +85°C



YF0028AA

4G adhesive mount FPC + cable dipole
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	698–2690 MHz
Efficiency	30%–75%
Peak gain	3.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	94 × 21 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	150 mm
Operation temperature	–40°C to +85°C



YF0022DA

4G adhesive mount PCB + cable monopole
embedded antenna
Compatible with Japan market

Compliant

RoHS & REACH

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	46% AVG.
Peak gain	2.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	15 × 40 × 0.8 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	74.5 mm
Operation temperature	–40°C to +85°C



YF0007KA

4G adhesive mount PCB + cable monopole
embedded antenna
Compatible with Japan market

Compliant


RoHS & REACH

Electrical data

Frequency range	600–960 MHz, 1427.9–1495.9 MHz, 1710–2690 MHz
Efficiency	58% AVG.
Peak gain	3.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	50 × 25 × 0.8 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	74.5 mm
Operation temperature	–40°C to +85°C



YPCA004AA

4G adhesive mount PCB + cable monopole
embedded antenna
Compatible with Japan market

Compliant

RoHS

Electrical data

Frequency range	698–960 MHz, 1710–2690 MHz
Efficiency	43% AVG.
Peak gain	2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	40 × 10 × 1.15 mm
Form factor	PCB + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YFCP002WWA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP002WWAEVB

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
35%~72%
3.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 42 × 10 × 3 mm, EVB: 131 × 60 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YFCP004WWA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP004WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz
27%–68%
2.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 40 × 7 × 3 mm, EVB: 136.5 × 43 × 1 mm
PCB chip
SMT
–40°C to +85°C



YFCP017WWA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP017WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz, 3300–3800 MHz
26%–66%
2.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 25 × 7 × 3 mm, EVB: 140 × 36 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YFCP017WWB

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP017WWBEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2690 MHz, 3300–3800 MHz
29%–73%
2.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 25 × 7 × 3 mm, EVB: 140 × 36 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YFCP005WWA

4G SMT Mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP005WWAEVB

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–960 MHz, 1710–2690 MHz
45% AVG.
2.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 36 × 9 × 3 mm, EVB: 126.5 × 45.5 × 0.8 mm
PCB chip
SMT
–40°C to +85°C



YFCP006WWA

4G SMT mount PCB chip IFA
embedded antenna
Compatible with Japan market

EVB

YFCP006WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1695–2200 MHz, 2300–2690 MHz
48% AVG.
2.9 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 28 × 8 × 3 mm, EVB: 130 × 36 mm
PCB chip
SMT
–40°C to +85°C



YFCH001WWA

4G Screw mount sheet metal + holder PIFA
embedded antenna
Compatible with Japan market

EVB

YFCH001WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

698–960 MHz, 1710–2700 MHz
45% AVG.
2.3 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 43.19 × 12.73 × 8.15 mm, EVB: 145 × 75 mm
Sheet metal + holder
Screw
–40°C to +85°C



YFCH002WWA

4G SMT mount sheet metal PIFA
embedded antenna
Compatible with Japan market

EVB

YFCH002WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

600–960 MHz, 1710–2690 MHz
22%–64%
2.6 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 40 × 7.23 × 7.6 mm, EVB: 136.5 × 43 mm
Sheet metal
SMT
–40°C to +85°C

EMBEDDED

Wi-Fi antennas



YC0009AA



YC0010AA



YFBC001WWA



YXU00A0AA



YF0026AA




YF0027AA



YF0029AA



YF0023HA





YC0009AA

Wi-Fi SMT mount ceramic chip IFA
embedded antenna

EVB

YC0009AAEVB

Compliant

RoHS

Electrical data

Frequency range

2400–2500 MHz

Efficiency

55%–70%

Peak gain

0.1 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 3.2 × 1.6 × 0.5 mm, EVB: 91 × 51 mm

Form factor


Ceramic chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YC0010AA

Wi-Fi SMT mount ceramic chip monopole
embedded antenna

EVB

YC0010AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range

2400–2500 MHz

Efficiency

55%–70%

Peak gain

3.8 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 5.2 × 2 × 1.2 mm, EVB: 90 × 50 mm

Form factor


Ceramic chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YXU00A0AA

Wi-Fi SMT mount PCB chip loop
embedded antenna
Compatible with Japan market

EVB

YXU00A0AAEVB

Compliant

RoHS

Electrical data

Frequency range

2400–2500 MHz; 5150–7125 MHz

Efficiency

45%–70%

Peak gain

3.6 dBi

Radiation pattern

omni-directional

Polarization

Linear

Mechanical data

Dimensions

Antenna: 8 × 6.6 × 1.6 mm, EVB: 60 × 50 × 1.6 mm

Form factor


PCB chip

Mounting type

SMT

Operation temperature

–40°C to +85°C



YFBC001WWA

Wi-Fi SMT mount ceramic chip loop embedded antenna

EVB

YFBC001WWAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
25%–65%
2.3 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

Antenna: 1.6 × 0.8 × 0.4 mm, EVB: 60 × 50 × 1 mm
Ceramic chip
SMT
–40°C to +85°C



YF0011KA

Wi-Fi adhesive mount FPC + cable dipole embedded antenna
Compatible with Japan market

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

2400–2500 MHz, 5150–5850 MHz
60%–80%
3.3 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

38.9 × 9 mm
FPC + cable
Adhesive
IPEX MHF1
RF1.13
50.5 mm
–40°C to +85°C



YF0011SA

Wi-Fi adhesive mount FPC + cable dipole embedded antenna

Compliant

RoHS

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

2400–2500 MHz, 5150–5850 MHz
40%–75%
3.1 dBi
omni-directional
Linear

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

38.9 × 9 mm
FPC + cable
Adhesive
IPEX MHF4L
RF1.13
100 mm
–40°C to +85°C



YF0026AA

Wi-Fi adhesive mount FPC + cable PIFA embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	50%–80%
Peak gain	6.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	28.9 × 11 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0026LA

Wi-Fi adhesive mount FPC + cable PIFA embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	50%–80%
Peak gain	5.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	28.9×11 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0027AA

Wi-Fi adhesive mount FPC + cable PIFA embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	45%–85%
Peak gain	6.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	38 × 7 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0027CA

Wi-Fi adhesive mount FPC + cable PIFA
embedded antenna

Compliant

RoHS

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	35%~70%
Peak gain	5.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	38×7 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0029AA

Wi-Fi adhesive mount FPC + cable PIFA
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	40%–80%
Peak gain	7.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	29.98×30.85 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0029CA

Wi-Fi adhesive mount FPC + cable PIFA
embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	40%–75%
Peak gain	6.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	29.98 × 30.85 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0023HA

Wi-Fi adhesive mount FPC + cable monopole embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 4900–5850 MHz, 5925–7125 MHz
Efficiency	45%–80%
Peak gain	6.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	22.7×11.9 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0023IA

Wi-Fi adhesive mount FPC + cable monopole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 4900–5850 MHz, 5925–7125 MHz
Efficiency	45%–85%
Peak gain	5.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	22.7×11.9 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0023FA

Wi-Fi adhesive mount FPC + cable monopole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 4900–5850 MHz, 5925–7125 MHz
Efficiency	55%–90%
Peak gain	7.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	37.8 × 7.5 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YF0023GA

Wi-Fi adhesive mount FPC + cable monopole
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	50%–85%
Peak gain	7.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data


Dimensions	37.8 × 7.5 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF4L
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C

EMBEDDED


Combo antennas



YFWO001AA




YFWO002AA



YFMA200E3AM





YFWO001AA

Wi-Fi 2in1 adhesive mount combo embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	2400–2500 MHz; 5150–7150 MHz
Efficiency	45%–75%
Peak gain	5.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	78.6 × 21.4 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YFCO002AA

5G 2in1 adhesive mount Combo embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	600–6000 MHz
Efficiency	35%–70%
Peak gain	5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	237 × 22 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	150 mm
Operation temperature	–40°C to +85°C



YFMA200E3AM

5G & Wi-Fi 2in1 adhesive mount Combo embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	5G × 1: 600–6000 MHz Wi-Fi × 1: 2400–2500 MHz, 5150–5850 MHz, 5925–7125 MHz
Efficiency	5G × 1: 33–76%; Wi-Fi × 1: 47–66%
Peak gain	5G × 1: 5 dBi; Wi-Fi × 1: 3.7 dBi
Radiation pattern	5G × 1: omni-directional; Wi-Fi × 1: omni-directional
Polarization	5G × 1: Linear; Wi-Fi × 1: Linear

Mechanical data


Dimensions	124.2 × 36.4 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	125 mm
Operation temperature	–40°C to +85°C

EMBEDDED

GNSS antennas



YC0013AA



YPGS001AA



YFGA003AA




YFGC025WWC



YFGC233WWA




YFGC007E3A



YFGN000H1AC



YFTA009E3AM





YC0013AA

GNSS L1 SMT mount ceramic chip passive embedded antenna

EVB

YC0013AAEVB

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	55%–65%
Peak gain	0.8 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 3.2 × 1.6 × 0.6 mm, EVB: 90 × 50 mm
Form factor	Ceramic chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YPGS001AA

GNSS L1 SMT mount PCB chip passive embedded antenna

EVB

YPGS001AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	51%–54%
Peak gain	1.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 7 × 5.8 × 0.8 mm, EVB: 80 × 35 × 0.8 mm
Form factor	PCB chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YCGS010AA

GNSS L1 & L2 & L5 & E6 SMT mount ceramic chip passive embedded antenna

EVB

YCGS010AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range	1164–1300 MHz, 1565–1586 MHz
Efficiency	L2/L5/E6/B3: 42%–50%, L1: 70%–74%
Peak gain	L2/L5/E6/B3: 1.3 dBi, L1: 2.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 5 × 3 × 0.5 mm, EVB: 80 × 40 mm
Form factor	Ceramic chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFGA003AA

GNSS L1 cable passive FPC + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	53%–55%
Peak gain	1.6 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	39.45 × 13.25 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	RF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YFGA005AA

GNSS L1 adhesive mount FPC + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	60%–65%
Peak gain	3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	61.15 × 11.24 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100.5 mm
Operation temperature	–40°C to +85°C



YFGA006AA

GNSS L1 & L2 & L5 & E6 adhesive mount FPC + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1164–1300 MHz, 1559–1606 MHz
Efficiency	40%–75%
Peak gain	3.9 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	74.5 × 24.5 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	143 mm
Operation temperature	–40°C to +85°C



YFGC009WWA

GNSS L1 SMT mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	23%–57%
Peak gain	0.9 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	15 × 15 × 4 mm
Form factor	Ceramic patch
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFGC009WWB

GNSS L1 SMT mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	42%–68%
Peak gain	2.1 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	18 × 18 × 4 mm
Form factor	Ceramic patch
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFGC009WWC

GNSS L1 SMT mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	70%–75%
Peak gain	3.9 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 4 mm
Form factor	Ceramic patch
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFGC010WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	20%-33%
Peak gain	0.1 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	10.2 × 10.2 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	-40°C to +85°C



YFGC012WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	20%-37%
Peak gain	-2.4 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	12 × 12 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & Soldering
Operation temperature	-40°C to +85°C



YFGC015WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	25%-65%
Peak gain	2.1 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	15 × 15 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	-40°C to +85°C



YFGC018WWCM

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1565–1606 MHz
Efficiency	35% AVG.
Peak gain	0.67 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	18 × 18 × 2 mm
Form factor	Ceramic patch
Mounting type	Adhesive & Soldering
Operation temperature	–40°C to +85°C



YFGC018WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	32%–68%
Peak gain	2.3 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	18 × 18 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC020WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	25%–70%
Peak gain	2.9 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	20 × 20 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC025WWC

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	60%–80%
Peak gain	3.6 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC025WWB

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	23%–60%
Peak gain	2.1 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 2 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC000WWAM

GNSS L1 & L5 adhesive & soldering mount ceramic patch passive embedded antenna with 1 pin

Compliant

RoHS & REACH

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 65%, L5: 44%
Peak gain	L1: 0.58 dBi, L5: –0.31 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 4 + 18 × 18 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC041WWAM

GNSS L1 & L5 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1164–1189 MHz, 1559–1606 MHz
L1: 39.2%, L5: 23.4%
L1: -0.6 dBi, L5: -2.5 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

25 × 25 × 2 + 18 × 18 × 2 mm
Ceramic patch
Adhesive & soldering
-40°C to +85°C



YFGC035WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1559–1606 MHz
72%–82%
4.4 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

35 × 35 × 4 mm
Ceramic patch
Adhesive & soldering
-40°C to +85°C



YFGC035WWB

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1559–1606 MHz
78%–83%
3.6 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

35 × 35 × 6 mm
Ceramic patch
Adhesive & soldering
-40°C to +85°C



YFGC040WWA

GNSS L1 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559–1606 MHz
Efficiency	66%–73%
Peak gain	4.3 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	40 × 40 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC238WWA

GNSS L1 & L5 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 45%–63%, L5: 40%–50%
Peak gain	L1: 3.9 dBi, L5: 1.4 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	38 × 38 × 6 + 28 × 28 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC233WWA

GNSS L1 & L5 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1164–1189 MHz, 1559–1606 MHz
Efficiency	L1: 45%–60%, L5: 40%–44%
Peak gain	L1: 2.3 dBi, L5: 0.7 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	33 × 33 × 4 + 25 × 25 × 4 mm
Form factor	Ceramic patch
Mounting type	Adhesive & soldering
Operation temperature	–40°C to +85°C



YFGC245WWB

GNSS L1 & L5 adhesive & soldering mount ceramic patch passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1164-1189 MHz, 1559-1606 MHz
L1: 52%-64%, L5: 55%-60%
L1: 4.4 dBi, L5: 2.9 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Operation temperature

45 × 45 × 8 + 40 × 40 × 4 mm
Ceramic patch
Adhesive & soldering
-40°C to +85°C



YFGA010E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1559-1606 MHz
14%-16%
-4.5 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

10.2 × 10.2 × 7.5 mm
Ceramic patch + cable
Buckle
IPEX MHF1
RF1.13
100 mm
-40°C to +85°C



YFGA012E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization

1559-1606 MHz
36%
-1.7 dBi
Directional
RHCP

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

12 × 12 × 7.5 mm
Ceramic patch + cable
Buckle
IPEX MHF1
RF1.13
100 mm
-40°C to +85°C



YFGA015E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	30%-46%
Peak gain	-1 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	15 × 15 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA018E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	44%-53%
Peak gain	-0.3 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	18 × 18 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA020E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	53.8% ~ 58.7%
Peak gain	0.4 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	20 × 20 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA025E3DM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	65%-74%
Peak gain	0.7 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA025E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	47%
Peak gain	-0.4 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 5.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA035E3BM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559 - 1606 MHz
Efficiency	75% ~ 81%
Peak gain	1.21 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	35 × 35 × 7.9 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA035E3DM

GNSS L1 buckle mount ceramic patch + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	78% ~ 83%
Peak gain	1.39 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	35 × 35 × 9.9 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA225E3BM

GNSS L1 & L5 screw mount ceramic patch + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	L1: 65%, L5: 44%
Peak gain	L1: 0.6 dBi, L5: -0.3 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	39 × 39 × 12.1 mm (25 × 25 × 4 + 18 × 18 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA235E3CM

GNSS L1 & L5 screw mount ceramic patch + cable passive embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	78%
Peak gain	2.69 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	50 × 50 × 12.2 mm (35 × 35 × 4 + 25 × 25 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA010E3AM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	14%-16%
Peak gain	-4.5 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	10.2 × 10.2 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA012E3AM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	36% AVG.
Peak gain	-1.7 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	12 × 12 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA015E3AM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	30%-46%
Peak gain	-1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	15 × 15 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA018E3AM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	44%-53%
Peak gain	-0.3 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	18 × 18 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA025E3CM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	65%-74%
Peak gain	0.7 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	25 × 25 × 7.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA025E3AM

GNSS L1 buckle mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1559-1606 MHz
Efficiency	45%-47%
Peak gain	-0.45 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	16 dB

Mechanical data

Dimensions	25 × 25 × 5.5 mm
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA225E3AM

GNSS L1 & L5 screw mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	L1: 55%-57%, L5: 35%-39%
Peak gain	L1: -0.2 dBi, L5: -1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	14 dB

Mechanical data

Dimensions	39 × 39 × 12.1 mm (25 × 25 × 4 + 18 × 18 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA233E3AM

GNSS L1 & L5 screw mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	L1: 28-59%, L5: 38.8%
Peak gain	2.64 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	50 × 50 × 12.2 mm (33 × 33 × 4 + 25 × 25 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGC007E3A

GNSS L1 & L5 buckle mount ceramic patch + cable active embedded antenna

Compliant


RoHS

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	L1: 32%-50%, L5: 50%-53%
Peak gain	L1: 1.2 dBi, L5: 1.1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	50 × 50 × 14.5 mm (38 × 38 × 6 + 25 × 25 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Buckle
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA245E3AM

GNSS L1 & L5 screw mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164-1189 MHz, 1559-1606 MHz
Efficiency	L1: 48.9-74%, L5: 54.9%
Peak gain	2.17 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	59 × 59 × 14.2 mm (45 × 45 × 6 + 40 × 40 × 4 mm)
Form factor	Ceramic patch + Cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA245E3BM

GNSS L2 & L5 screw mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1217-1238 MHz, 1559-1606 MHz
Efficiency	L1: 46%-73%, L2: 58%-61%
Peak gain	L1: 3.5 dBi, L2: 2 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	59 × 59 × 14.2 mm (45 × 45 × 6 + 40 × 40 × 4 mm)
Form factor	Ceramic patch + Cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGA245E3CM

GNSS L1 & L2 & L5 screw mount ceramic patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164-1238 MHz, 1559-1606 MHz
Efficiency	L1: 50%-76%, L2/L5: 28%-35%
Peak gain	L1: 3.6 dBi, L2/L5: -1 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	17 dB

Mechanical data

Dimensions	59 × 59 × 16.2 mm (45 × 45 × 8 + 40 × 40 × 4 mm)
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



YFGN001H3AM

GNSS full band screw mount PPO patch + cable active embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1164–1300 MHz, 1525–1606 MHz
Efficiency	Lower Band: 58%; L-band: 45.2%; Upper Band: 67%
Peak gain	Lower Band: 5.6 dBi; L-band: 3.1 dBi; Upper Band: 5.4 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	40 ±4 dB

Mechanical data

Dimensions	Ø122 × 24.2 mm
Form factor	PPO Patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	220 mm
Operation temperature	–40°C to +85°C



YFGD000AA

GNSS full band screw mount PPO patch + cable active embedded antenna

Compliant


RoHS & REACH & POPS

Electrical data

Frequency range	1164–1300 MHz, 1525–1606 MHz
Efficiency	Lower Band: 50%; L-band: 38%; Upper Band: 53%
Peak gain	Lower Band: 3.7 dBi; L-band: 1.5 dBi; Upper Band: 3.5 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	38 ±4 dB

Mechanical data

Dimensions	78.6 × 75.6 × 16.2 mm
Form factor	PPO Patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	89 mm
Operation temperature	–40°C to +85°C



YFGD000BA

GNSS L1 & L2 & L5 screw mount PPO patch + cable active embedded antenna

Compliant


RoHS & REACH & POPS

Electrical data

Frequency range	1164–1238 MHz, 1559–1606 MHz
Efficiency	L1: 51.8%–65.1%; L2: 45.7%; L5: 63.2%–71.3%
Peak gain	L1: 1.87 dBi; L2: 2.07 dBi; L5: 2.15 dBi
Radiation pattern	Directional
Polarization	RHCP
LNA gain	38 ±4 dB

Mechanical data

Dimensions	78.6 × 75.6 × 16.2 mm
Form factor	PPO Patch + Cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.37
Cable length	89 mm
Operation temperature	–40°C to +85°C



YFGN000H1AC

GNSS full band screw mount Air Dielectric + cable active embedded antenna

Compliant

RoHS & REACH

Electrical data


Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization
LNA gain

1164–1300 MHz, 1525–1606 MHz
Lower Band: 38.8%–54.9%; L-band: 58.5%; Upper Band: 52.9%–65.6%
Lower Band: 5.02 dBi; L-band: 5.02 dBi; Upper Band: 5.54 dBi
Directional
RHCP
35 ±4 dB

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

Ø 122 × 22.5 mm
Air Dielectric + Cable
Screw
SMA male
RG174
300 mm
–40°C to +85°C



YFGN000H1CC

GNSS full band screw mount Air Dielectric + cable active embedded antenna

Compliant

RoHS

Electrical data

Frequency range
Efficiency
Peak gain
Radiation pattern
Polarization
LNA gain

1164–1300 MHz, 1559–1606 MHz
55% AVG.
5.7 dBi
Directional
RHCP
35 ±4 dB

Mechanical data

Dimensions
Form factor
Mounting type
Connector type
Cable type
Cable length
Operation temperature

Ø 122 × 22.5 mm
Air Dielectric + Cable
Screw
SMA male
RG174
300 mm
–40°C to +85°C



YFTC025WWAM

NTN adhesive & soldering mount ceramic patch passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	1627–1653 MHz
Efficiency	75% AVG.
Peak gain	4.86 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	25 × 25 × 4 mm
Form factor	Ceramic Patch
Mounting type	Adhesive & Soldering
Operation temperature	–40°C to +85°C



YFTN005E3AM

NTN screw mount PCB + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	TX: 1626.5–1660.5 MHz RX: 1525–1559 MHz
Efficiency	55% AVG.
Peak gain	2.74 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	80.0 × 80.0 × 19.0 mm
Form factor	PCB + Cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YFTN005E3BM

NTN screw mount PCB + cable passive embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	Iridium: 1616–1626.5 MHz L-Band: TX: 1626.5–1660.5 MHz RX: 1525–1559 MHz
Efficiency	60% AVG.
Peak gain	4.44 dBi
Radiation pattern	Directional
Polarization	RHCP

Mechanical data

Dimensions	80.0 × 80.0 × 11.0 mm
Form factor	Ceramic patch + cable
Mounting type	Screw
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	–40°C to +85°C



YFTA009E3AM

L-Band & GNSS L1 & iridium screw mount
ceramic patch + cable passive
embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range

Efficiency

Peak gain

Radiation pattern

Polarization

GNSS: 1559–1606 MHz,
L-Band: 1518–1559 MHz,1626–1660 MHz,1668–1675 MHz
Iridium: 1616–1626.5 MHz
GNSS: 75%-80%, L-Band: 60%-91%, Iridium: 87%
GNSS: 5.3 dBi, L-Band: 5.6 dBi, Iridium: 2.38 dBi
Directional
RHCP

Mechanical data

Dimensions

Form factor

Mounting type

Connector type

Cable type


Cable length

Operation temperature

80 × 80 × 13.3 mm (50 × 50 × 10 mm)
Ceramic patch + cable
Screw
IPEX MHF1
RF1.13
100 mm
–40°C to +85°C

EMBEDDED

LPWA/ISM antennas



YCIS002AA



YCIS003AA



YSIS001AA



YPCS002AA



YMCP003AA




YFOA004AA




YFNF915F3AM



YFNF868F3AM





YCIS002AA

LPWA/ISM SMT mount ceramic chip IFA embedded antenna

EVB

YCIS002AAEVB

Compliant


RoHS

Electrical data

Frequency range	863–870 MHz
Efficiency	40%~60%
Peak gain	0.7 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 10 × 3.2 × 0.5 mm, EVB: 80 × 40 mm
Form factor	Ceramic chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YCIS003AA

LPWA/ISM SMT mount ceramic chip IFA embedded antenna

EVB

YCIS003AAEVB

Compliant


RoHS

Electrical data

Frequency range	902–928 MHz
Efficiency	35%~70%
Peak gain	1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 10 × 3.2 × 0.5 mm, EVB: 80 × 40 mm
Form factor	Ceramic chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFNP017WWA

LPWA/ISM SMT mount PCB chip monopole embedded antenna

EVB

YFNP017WWAEVB

Compliant


RoHS & REACH

Electrical data

Frequency range	790–960 MHz
Efficiency	40%~60%
Peak gain	0.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 25 × 7 × 3 mm, EVB: 105.53 × 25 × 0.8 mm
Form factor	PCB chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YPCS002AA

LPWA/ISM SMT mount PCB chip monopole embedded antenna

EVB

YPCS002AAEVB

Compliant

RoHS & REACH

Electrical data

Frequency range	791–960 MHz
Efficiency	20%–35%
Peak gain	1.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 20 × 11 × 1.6 mm, EVB: 115 × 35 × 0.8 mm
Form factor	PCB chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFNP002WWAM

LPWA/ISM SMT mount PCB chip monopole embedded antenna

EVB

YFNP002WWAMEVB

Compliant

RoHS & REACH

Electrical data

Frequency range	433–435 MHz
Efficiency	0.158
Peak gain	–4.9dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 17 × 4 × 1.5mm, EVB: 197.7 × 92 × 1mm
Form factor	PCB Chip
Mounting type	SMT
Operation temperature	–40°C to +85°C



YSIS001AA

LPWA/ISM SMT mount spring + holder monopole embedded antenna

EVB

YSIS001AAEVBAA

Compliant

RoHS & REACH & TSCA

Electrical data

Frequency range	412–427 MHz, 433–435 MHz, 450–470 MHz
Efficiency	25% AVG.
Peak gain	0.4 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 30 × 7 × 7 mm, EVB: 185 × 90 × 1 mm
Form factor	Spring + holder
Mounting type	SMT
Operation temperature	–40°C to +85°C



YMCP003AA

LPWA/ISM SMT mount sheet metal PIFA embedded antenna

EVB

YMCP003AAEVBAA

Compliant

RoHS & REACH

Electrical data

Frequency range	790–960 MHz
Efficiency	60%–70%
Peak gain	1.1 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	Antenna: 40.99 × 6.68 × 3.99 mm, EVB: 135 × 45 mm
Form factor	Sheet metal
Mounting type	SMT
Operation temperature	–40°C to +85°C



YFNF915F3AM

LPWA/ISM adhesive mount FPC + cable dipole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	915 MHz
Efficiency	70%–73%
Peak gain	2.5 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	120.2 × 25 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF 1
Cable type	RF1.13
Cable length	150 mm
Operation temperature	–40°C to +85°C



YFNF868F3AM

LPWA/ISM adhesive mount FPC + cable PIFA embedded antenna

Compliant


RoHS & REACH

Electrical data

Frequency range	868 MHz
Efficiency	65%–70%
Peak gain	1.3 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	70 × 40 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF 1
Cable type	RF1.13
Cable length	150 mm
Operation temperature	–40°C to +85°C



YFOA004AA

LPWA/ISM adhesive mount FPC + cable
monopole embedded antenna

Compliant

RoHS & REACH

Electrical data

Frequency range	410~470 MHz
Efficiency	45%~54%
Peak gain	0.2 dBi
Radiation pattern	omni-directional
Polarization	Linear

Mechanical data

Dimensions	100×20 mm
Form factor	FPC + cable
Mounting type	Adhesive
Connector type	IPEX MHF1
Cable type	RF1.13
Cable length	100 mm
Operation temperature	-40°C to +85°C



Product name

DC~6 GHz SMA female to IPEX MHF1 cable with an O-ring

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

IPEX MHF1

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

YSAN025AA

YSAN025BA

YSAN025CA

YSAN025DA

YSAN025EA

Cable length

100 mm

150 mm

200 mm

250 mm

300 mm



Product name

DC~6 GHz SMA female to IPEX MHF1 cable

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

IPEX MHF1

Cable type

RF1.13

Operation temperature

-40°C to +85°C

OC

YLUN025EQAM

YLUN025FQAM

YLUN025GQAM

YLUN025JQAM

Cable length

100 mm

150 mm

200 mm

300 mm



Product name

DC~6 GHz SMA female to RF1 cable

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

RF1

Cable type

RF1.13

Operation temperature

-40°C to +85°C

OC

YLUP025E2AC-CN

YLUP025F2AC-CN

YLUP025G2AC-CN

YLUP025J2AC-CN

Cable length

100 mm

150 mm

200 mm

300 mm



Product name

DC~6 GHz RP SMA female to IPEX MHF1 cable with an O-ring

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

RP SMA female

Connector type2

IPEX MHF1

Cable type

RF1.13

Operation temperature

-20°C to +85°C

OC

YSAN026AA

YSAN026BA

YSAN026CA

YSAN026DA

YSAN026EA

Cable length

100 mm

150 mm

200 mm

250 mm

300 mm



Product name

DC~6 GHz SMA female to IPEX MHF4L cable with an O-ring

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

IPEX MHF4L

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

YSAN027AA

YSAN027BA

YSAN027CA

YSAN027DA

YSAN027EA

Cable length

100 mm

150 mm

200 mm

250 mm

300 mm



Product name

DC~6 GHz SMA female to IPEX MHF4L cable

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

IPEX MHF4L

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

YLUN026EQAM

YLUN026FQAM

YLUN026GQAM

YLUN026HQAM

YLUN026JQAM

YLUN026KQAM

Cable length

100 mm

150 mm

200 mm

250 mm

300 mm

500 mm



Product name

DC~6 GHz SMA female to RF4 cable

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA female

Connector type2

RF4

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

Cable length

YLUP027E2AC-CN 100 mm

YLUP027F2AC-CN 150 mm

YLUP027G2AC-CN 200 mm

YLUP027J2AC-CN 300 mm



Product name

DC~6 GHz RP SMA female to IPEX MHF4L cable with an O-ring

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

RP SMA female

Connector type2

IPEX MHF4L

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

Cable length

YSAN028AA 100 mm

YSAN028BA 150 mm

YSAN028CA 200 mm

YSAN028DA 250 mm

YSAN028EA 300 mm



Product name

DC~6 GHz RP SMA female to IPEX MHF4L cable

Compliant

RoHS

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

RP SMA female

Connector type2

IPEX MHF4L

Cable type

RF1.13

Operation temperature

-40°C to +80°C

OC

Cable length

YSAN028FA 100 mm

YSAN028GA 150 mm

YSAN028HA 200 mm

YSAN028IA 250 mm

YSAN028JA 300 mm



Product name

DC~6 GHz SMA male to SMA female cable with LMH mark

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA male

Connector type2

SMA female

Cable type

ALSR200

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX013XQA 700 mm

YLUX013XQD 1700 mm

YLUX013XQG 2700 mm

YLUX013XQK 4700 mm



Product name

DC~6 GHz SMA male to SMA female cable with MH mark

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA male

Connector type2

SMA female

Cable type

ALSR200

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX013XQB 700 mm

YLUX013XQE 1700 mm

YLUX013XQH 2700 mm

YLUX013XQL 4700 mm



Product name

DC~6 GHz SMA male to SMA female cable with Wi-Fi mark

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA male

Connector type2

SMA female

Cable type

ALSR200

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX013XQC 700 mm

YLUX013XQF 1700 mm

YLUX013XQJ 2700 mm

YLUX013XQM 4700 mm



Product name

DC~2GHz SMA male to
SMA female cable with
GNSS mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~2 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type RG174

Operation temperature -40°C to +85°C

OC

YLUX013XQN

Cable length

700 mm

YLUX013XQP

1 700 mm

YLUX013XQQ

2 700 mm

YLUX013XQR

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
LMH mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~6 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type ALS302

Operation temperature -40°C to +85°C

OC

YLUX016XQA

Cable length

700 mm

YLUX016XQD

1 700 mm

YLUX016XQG

2 700 mm

YLUX016XQK

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
MH mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~6 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type ALS302

Operation temperature -40°C to +85°C

OC

YLUX016XQB

Cable length

700 mm

YLUX016XQE

1 700 mm

YLUX016XQH

2 700 mm

YLUX016XQL

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
Wi-Fi mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~6 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type ALS302

Operation temperature -40°C to +85°C

OC

YLUX016XQC

Cable length

700 mm

YLUX016XQF

1 700 mm

YLUX016XQJ

2 700 mm

YLUX016XQM

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
LMH mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~6 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type RG405

Operation temperature -40°C to +85°C

OC

YLUX017XQA

Cable length

700 mm

YLUX017XQD

1 700 mm

YLUX017XQG

2 700 mm

YLUX017XQK

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
MH mark

Compliant

RoHS & REACH

Electrical data

Frequency range DC~6 GHz

Mechanical data

Connector type1 SMA male

Connector type2 SMA female

Cable type RG405

Operation temperature -40°C to +85°C

OC

YLUX017XQB

Cable length

700 mm

YLUX017XQE

1 700 mm

YLUX017XQH

2 700 mm

YLUX017XQL

4 700 mm



Product name

DC~6 GHz SMA male to
SMA female cable with
Wi-Fi mark

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA male

Connector type2

SMA female

Cable type

RG405

Operation temperature

-40°C to +85°C

OC


Cable length

YLUX017XQC 700 mm

YLUX017XQF 1700 mm

YLUX017XQJ 2700 mm

YLUX017XQM 4700 mm



Product name

DC~6 GHz fakra female
Code C to SMA female
cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

Fakra female Code C

Connector type2

SMA female

Cable type

RG174

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX030LLAM 700 mm

YLUX031NLAM 1700 mm

YLUX032QLAM 2700 mm

YLUX033ULAM 4700 mm



Product name

DC~6 GHz fakra female
Code D to SMA female
cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

Fakra female Code D

Connector type2

SMA female

Cable type

RG174

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX034LLAM 700 mm

YLUX035NLAM 1700 mm

YLUX036QLAM 2700 mm

YLUX037ULAM 4700 mm



Product name

DC~6 GHz fakra female
Code D to SMA female
cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

Fakra female Code D

Connector type2

SMA female

Cable type

ALSR100

Operation temperature

-40°C to +85°C

OC

Cable length

YLUX038LLAM 700 mm

YLUX039NLAM 1700 mm

YLUX040QLAM 2700 mm

YLUX041ULAM 4700 mm



Product name

DC~6 GHz SMA male to
TNC male cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

SMA male

Connector type2

TNC male

Cable type

RG174

Operation temperature

-40°C to +85°C

OC

Cable length

YEGX000Q1AM 3000 mm



Product name

DC~6 GHz IPEX MHF1 to
N type female cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

IPEX MHF1

Connector type2

N type female

Cable type

RG178

Operation temperature

-40°C to +80°C

OC

Cable length

YLUN001GQAH 200 mm



Product name

DC~6 GHz IPEX MHF1 to
TNC male cable

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6 GHz

Mechanical data

Connector type1

IPEX MHF1

Connector type2

TNC male

Cable type

RG178

Operation temperature

-40°C to +80°C

OC

Cable length

YLUN002GQAH 200 mm



Product name

DC~9GHz IPEX MHF1
receptacle connector

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~9GHz

Mechanical data

Dimensions

3.1 × 3 × 1.25 mm

Connector type1

IPEX MHF1

Operation temperature

-40°C to +85°C

OC

YSLT001W3AM



Product name

DC~6GHz RF1 receptacle
connector

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6GHz

Mechanical data

Dimensions

3.1 × 3 × 1.25 mm

Connector type1

RF1

Operation temperature

-40°C to +85°C

OC

YSLT001W3BM



Product name

DC~6GHz IPEX MHF4
receptacle connector

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6GHz

Mechanical data

Dimensions

2 × 2 × 0.6 mm

Connector type1

IPEX MHF4

Operation temperature

-40°C to +85°C

OC

YSLT004W4AM



Product name

DC~6GHz RF4 receptacle
connector

Compliant

RoHS & REACH

Electrical data

Frequency range

DC~6GHz

Mechanical data

Dimensions

2.1 × 2.05 × 0.6 mm

Connector type1

RF4

Operation temperature

-40°C to +85°C

OC

YSLT004W3BM



Product name

DC~6GHz SMA female
connector

Compliant

RoHS

Electrical data

Frequency range

DC~6GHz

Mechanical data

Dimensions

6.5 × 6.5 × 13.5 mm

Connector type1

SMA female

Operation temperature

-40°C to +85°C

OC

YSLT006W2AM



Product name

DC~6GHz right angle SMA
female connector

Compliant

RoHS

Electrical data

Frequency range

DC~6GHz

Mechanical data

Dimensions

14.5 × 13 × 6 mm

Connector type1

right angle SMA female

Operation temperature

-40°C to +85°C

OC

YSLT006W2BM



YAXX001XXA

Accessory-Bracket

Compliant

RoHS & REACH


Mechanical data

Dimensions

82.2 × 60.31 × 48 mm

Operation temperature

-40°C to +85°C



YBY00A0IA

Accessory-Bracket

Compliant

RoHS

Mechanical data

Dimensions

80 × 60 × 86 mm

Operation temperature

-20°C to +85°C



YEGM003WWAM

Accessory-Bracket

Compliant

RoHS

Mechanical data

Dimensions

Φ108×123 mm

Operation temperature

-40°C to +85°C

Custom antenna design services

In addition to standard products, Quectel also provide full-process customized antenna services. Tailored to your equipment performance requirements and production scenarios, Quectel can design bespoke antenna solutions that cover the entire lifecycle, including performance optimization, structural adaptation, manufacturing, and assembly. These solutions precisely address core challenges such as signal issues and spatial adaptation, helping your equipment achieve superior communication performance and production efficiency.



NFC antenna



NFC antenna




Spring antenna



LDS antenna



Transparent antenna




Sheet metal antenna



PCB antenna




Combo antenna



Combo antenna



Stacked patch antenna



Stacked patch antenna



Fiberglass antenna



Rubber antenna



Cable



Connector



Build a smarter world




An end-to-end IoT solutions provider with a unique global footprint and unmatched scale



HARDWARE

Our vast portfolio of modules, antennas, EVKs and smart solutions cover every connectivity type and form factor to ensure you find the ideal model for your needs



SOFTWARE

Achieve rapid application development with our modules using simple Python code execution with our flexible OpenCPU solution QuecPython



SERVICES

We offer expert support across the development cycle - from antenna and RTK support to security, testing, certification, ODM and manufacturing

For more information please visit [Quectel.com](https://www.quectel.com)

Europe

Czech Republic: Prague
Denmark: Copenhagen
France: Nice/Paris
Germany: Augsburg/Berlin/Hannover/Munich
Ireland: Navan
Italy: Casatenovo/Milan
Poland: Gdynia/Warsaw/Wroclaw
Serbia: Belgrade

Slovenia: Ljubljana
Spain: Barcelona
Sweden: Sollentuna/Stockholm
Switzerland: Zurich
The Netherlands: Eindhoven
Turkey: Istanbul
UK: Birmingham/London/Manchester/Oxford

North America

Canada:
 Mississauga/Toronto, ON
 Vancouver, B.C.

United States:
 Alpharetta, GA
 Chicago, IL
 Houston/Round Rock/San Marcos, TX
 Irvine/Orange County/San Diego/
 Scotts Valley/Silicon Valley, CA
 Point Roberts, WA



China
 Quectel Global Center

Latin America

Argentina: Buenos Aires
Brazil: Sao Paulo
Mexico: Mexico City / Queretaro

Israel / Africa

Israel: Tel Aviv
South Africa: Gauteng/Johannesburg
Egypt: Cairo

Asia Pacific

Australia: Melbourne/Sydney
India: Bangalore/Delhi/Hyderabad/Mumbai
Indonesia: Bandung/Jakarta
Japan: Tokyo
Korea: Seoul
Malaysia: Penang

Pakistan: Lahore
Philippines: Manila/Pasay City
Singapore
Thailand: Bangkok/Samutprakarn
Vietnam: Hanoi/Ho Chi Minh City

50+ sales offices
8 R&D centers globally
90+ distributors
Serving 7000+ customers

Overseas

Africa Email: africa-sales@quectel.com ANZ Email: anz-sales@quectel.com Benelux Email: benelux-sales@quectel.com Brazil Email: brazil-sales@quectel.com CIS Email: cis-sales@quectel.com DACH Email: dach-sales@quectel.com	East-Europe Email: east-europe-sales@quectel.com France Email: france-sales@quectel.com Iberia Email: iberia-sales@quectel.com India Email: india-sales@quectel.com Israel Email: israel-sales@quectel.com Italy Email: italy-sales@quectel.com	Japan Email: japan-sales@quectel.com Korea Email: korea-sales@quectel.com Latin America Email: latinamerica-sales@quectel.com Middle East Email: middleeast-sales@quectel.com Nordic Email: nordic-sales@quectel.com	North America Email: northamerica-sales@quectel.com S.E.A Email: sea-sales@quectel.com South East Europe Email: see-sales@quectel.com Turkey Email: turkey-sales@quectel.com UK & Ireland Email: uk-sales@quectel.com
--	--	--	---

Quectel Global Center

No. 8 Waipojing Road, Sijing Town,
 Songjiang District, Shanghai 201601, China
 Tel: +86 21 5108 6236

Hefei R&D Center

Building 1-C, China Speech Valley Area A, 3335 Xiyu Road,
 High-tech Zone, Hefei, Anhui 230088, China
 Tel: +86 551 6586 9386

Vancouver R&D Center

13551 Commerce Pkwy Unit 100,
 Richmond, BC Canada

Shanghai R&D Center

No. 8 Waipojing Road, Sijing Town,
 Songjiang District, Shanghai 201601, China
 Tel: +86 21 5108 6236

Foshan R&D Center

Floor 9, Building 2, Sanshan Science and Technology Innovation Center, No. 12,
 Gangkou Road, Sanshan New City, Guicheng Street, Nanhai District, Foshan,
 Guangdong 528200, China
 Tel: +86 757 6663 6236

Belgrade R&D Center

3rd Floor, Danube Business Center, Bulevar Mihaila Pupina 10L,
 11070 New Belgrade, Serbia

Guilin R&D Center

Floor 4, Building 9, Guilin Electric Valley, Chaoyang Road,
 Qixing District, Guilin, Guangxi 541004, China
 Tel: +86 773 5886 236

Wuhan R&D Center

Floor 4-5, A2 Huaxiang Center, 776 Gaoxin Avenue, Donghu New Technology
 Development Zone, Hongshan District, Wuhan City, Hubei 430074, China
 Tel: +86 027 6552 5933

Penang R&D Center

1C-1-01 One Precinct, Lengkok Mayang Pasir, 11900 Bayan Lepas, Pulau
 Pinang, Malaysia